

# 15.6 Inch Windows/Android Touch POS Terminal

(M/N:POS-1566)

## Features:

- 15.6 inch BOE brand new LCD screen
- Multi-point projected capacitive touch panel
- Removable bottom plate for smaller packaging and less shipping cost
- The main screen supports large angle rotation to meet any observation angle
- Border-less screen , the front protects against direct water splashes
- Ultra-thin body makes the product more concise and stylish
- Thick and stable aluminum base
- Cable slots inside the base make the cable more tidy
- Customer display, secondary screen and MSR installation position is reserved on the shell

## Specification

Model	POS-1566-W
Name	15.6 inch Windows touch screen POS terminal
Main screen	15.6 inch touch screen monitor
Resolution	1366*768, 1920*1080 for option
Brightness	250cd/m <sup>2</sup>
View angle	Horizon: 160; Vertical :150
Touch screen	Multi-point projected G+G capacitive touch
Sub-display	11.6inch display W or W/o touch function, resolution 1366*768
Customer display	2*20 VFD mounted to back cover for option
<b>Performance</b>	
Motherboard	Intel Core I5 4 <sup>th</sup> CPU,other CPU need to be customized
System Memory	2*SO-DIMM DDR3L 1333/1600MHz 4GB , up to 16GB
Storage device	Msata SSD 128GB or higher, up to 512GB
Audio	On board Real-tech chip
LAN	10//100/1000Mbs, 1*Realtek RTL8111 LAN chip built in Mini PCI-E slot,support embedded WIFI module
Optional WIFI&BT	2.4G&5G WIFI ,BT 5.0 supported for option
Speaker	4ohm/2w*1
Operating System	Support win10 /win11
<b>Connectivity</b>	

External I/O port (I5 4 <sup>th</sup> )	power button*1
	12V DC in jack*1
	LAN:RJ-45*1
	2*USB3.0□4*USB2.0
	COM(RS232) * 1
	1*HDMI
	Audio out*1□1*Mic-in
<b>Package</b>	
Weight	Net 3.5kg(without power adaptor and power cord)
Package with foam inside	470*180*400mm/4.6kg
2 in1 box	485*365*405mm/10kg
<b>Environment</b>	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
<b>Accessories</b>	
Power adapter	100-240V/50-60HZ 1.5Amax AC power input ,DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available

