15.6 or 15.1 Inch All In One Touch POS Terminal

(M/N:POS-H156/H151)

OCOM H series pos integrated high speed thermal printer and scanner module inside, it is a kind of cost-effective machine for using, different frame colors make machine more beautiful,

extended IO interface make a few more external devices connected, newly designed rear cover which can be easily removed without tools for faster installation and maintenance

Features:

- * Intel Celeron series and intel core I3 I5 processor for optional
- *Hard Driver Msata SSD 64GB ,SSD 128GB an 256 GB for optional
- * 58mm and 80mm high speed thermal printer built in for optional
- *Multi-point projected capacitive touch panel
- *Optional side MSR and VFD220 customer display mounted to back cover
- *Bar-code scanner inbuilt for option
- *True flat and water-proof/scratch-resistant sureface display

Specification

Model	POS-H156	POS-H151				
Name	15.6 inch all in one touch screen pos terminal	15.1 inch all in one touch screen pos terminal				
Housing	plastic with metal combined	plastic with metal combined				
Color	white machine body or black machine body match orange or blue frame colors					
Display						
Main screen	15.6 inch touch screen monitor	nch touch screen monitor 15.1 inch touch screen monitor				
Resolution	1366*768	1024*768				
Brightness	250cd/m ²					
View angle	Horizon: 150; Vertical :140					
Touch screen	Multi-point projected G+G capacitive touch					
Sub-display	15.6/14 and 11.6 inch display W/ or W/o touch function, resolution 1366*768 for optional	15.1 inch display W/ or W/o touch function, resolution 1024*768				
Customer display	2*20 VFD mounted to back cover for option	2*20 VFD mounted to back cover for optional				
performance						
Motherboard	Intel Celeron Bay Trail J1900 2.0GHz or intel core I3 / I5 4 th generation CPU for optional					
System Memory	1*SO-DIMM DDRIII slot, support1333*/1600 2GB/4GB/8GB for optional					
Storage device	Msata SSD 64GB or higer, up to 256GB					
Audio	On board Real Tek ALC662 audio chip					
Speaker	4ohm/5w speakers inside for optional					

LAN	10/100Mbs,Realtek RTL8111F Lan chip built in Mini PCI-E slot,support embedded WIFI module		
Operating System	Windows7/8/10, Embedded,WEPOS,Linux		
Connectivity			
External I/O port(J1900)	power button*1		
	12V DC in jack*1		
	COM(RS232) *1 or HDMI*1 for optional		
	VGA(15Pin D-sub)*1		
	LAN:RJ-45*1 ,RJ11 for Cash drawer *1		
	USB 3.0*1,USB2.0*5		
	MIC in*1, Audio out*1		
Options	The III 1, riddle out 1		
80mm thermal printer	direct thermal printing		
	100mm/s pringting speed		
	79.5-/+ 0.5mm paper width and printable width 72mm		
	with atuo cutter function and thermal head life 50km		
	LPT communication		
58mm thermal printer	direct thermal printing		
Sommer enerman princer	85mm/s pringting speed		
	57.5-/+ 0.5mm paper width and printable width 48mm		
	thermal head life 50km		
	LPT communication		
MSR	optional side MSR		
Web camera	web camera mounted on top of the display for optional		
Scanner	support 1D&2D code-scanning for optional		
Package	package		
Weight	net 5.6Kg gross: 7.7Kg for 15.6 with 15.6 dual screen /no printer built in		
Package with foam inside	340*450*480mm		
2in1 carton	700*460*500mm /gross∏17Kg		
Environment			
Operating temperature	0 to 40 degrees centigrade		
Storage temperature	-10 to 60 degrees centigrade		
Working humidity	10%~80%		
Storage humidity	10%~90%		
Accessories			
Power adapter	110-240V/50-60HZ AC powerinput ,DC12/5A output adaptor for W/o printer and W/		
, 	58mm printer machine DC12V/7A out put adaptor only for W/ 80mm printer machine		
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available		
CD driver	Motherboard driver and touch driver inside		
Other			
Compliance	FCC Class A/CE Mark/LVD/CCC		











Package











