

15.6 Inch Windows Efficiency POS Terminal

(M/N:POS-1566)

OCOM Wide-screen POS terminal has stylish and ultra slim body design, It has Android and Windows OS motherboard for option, it is easy to install 2nd display, MSR or VFD as modules by customers. This model is very convenient for maintenance by removing the back cover and it has rich I/O interfaces to be connected to more external devices

Features:

- l. 15.6 inch BOE brand new LCD screen
- m. Multi-point projected capacitive touch panel
- n. Removable bottom plate for smaller packaging and less shipping cost
- o. The main screen supports large angle rotation to meet any observation angle
- p. Border-less screen, the front protects against direct water splashes
- q. Ultra-thin body makes the product more concise and stylish
- r. Thick and stable aluminum base
- s. Cable slots inside the base make the cable more tidy
- t. Customer display, secondary screen and MSR installation position is reserved on the shell

Specification

Model	POS-1566-W
Name	15.6 inch Windows touch screen POS terminal
Main screen	15.6 inch touch screen monitor
Resolution	1366*768, 1920*1080 for option
Brightness	250cd/m ²
View angle	Horizon: 160; Vertical :150
Touch screen	Multi-point projected G+G capacitive touch
Sub-display	11.6inch display W or W/o touch function, resolution 1366*768
Customer display	2*20 VFD mounted to back cover for option
Performance	
Motherboard	Intel Core i5 4 th CPU, other CPU need to be customized
System Memory	2*SO-DIMM DDR3L 1333/1600MHz 4GB, up to 16GB
Storage device	M SATA SSD 128GB or higher, up to 512GB
Audio	On board Real-tech chip
LAN	10//100/1000Mbps, 1*Realtek RTL8111 LAN chip built in Mini PCI-E slot, support embedded WIFI module
Optional WIFI&BT	2.4G&5G WIFI, BT 5.0 supported for option
Speaker	4ohm/2w*1
Operating System	Support win10 /win11
Connectivity	
External I/O port (i5 4 th)	power button*1
	12V DC in jack*1
	LAN:RJ-45*1
	2*USB3.0□4*USB2.0
	COM(RS232) * 1
	1*HDMI
	Audio out*1□1*Mic-in
Package	
Weight	Net 3.5kg(without power adaptor and power cord)
Package with foam inside	470*180*400mm/4.6kg
2 in1 box	485*365*405mm/10kg

Environment	
Operating temperature	0 to 40 degrees centigrade
Storage temperature	-10 to 60 degrees centigrade
Working humidity	10%~80% No condensation
Storage humidity	10%~90% No condensation
Accessories	
Power adapter	100-240V/50-60HZ 1.5Amax AC power input ,DC12V/5A output adaptor
Power cable	Power cable plug compatible with USA /EU / UK etc and customized available

