

## 19-inch Touch Screen LCD Display

(Model No: TM1901)

### Features:



Multifunctional setting key;

5 or 4 wire touch panel for option;

Grade A LCD panel with LED backlight;

High resolution 1280\*1024@60HZ;

Suitable for all kinds of high-intensity working environment.

### Specification

|          |                                                              |
|----------|--------------------------------------------------------------|
| Model    | TM-1901                                                      |
| Name     | 19 inch touch screen display                                 |
| Color    | Whole black color machine usually                            |
| Material | Metal base with plastic body                                 |
| VESA     | 75*75mm for wall mounting(need extral wall mounting bracket) |

|                           |                                                                                                                           |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------|
| OSD Language              | Support 8kinds of international languages                                                                                 |
| Display                   |                                                                                                                           |
| Display area              | 376.32(W)×301.056(H) mm                                                                                                   |
| Pixel pitch               | 0.294*0.294                                                                                                               |
| Aspect ratio              | 4:3                                                                                                                       |
| Resoluiton                | 1280*1024                                                                                                                 |
| Brightness                | 300cd/m2                                                                                                                  |
| Contrast                  | 1000:1                                                                                                                    |
| Display color             | 16.7M                                                                                                                     |
| View angle                | Horizon: 170; Vertical :160                                                                                               |
| Response time             | 5ms                                                                                                                       |
| Touch function            |                                                                                                                           |
| Touch screen              | 5-wire resistive touch panel,4-wiretouch screen for option                                                                |
| Structure                 | ITO Film and ITO Glass FIT                                                                                                |
| surface treatment         | Fog surface, anti-glare                                                                                                   |
| Responding speed          | <5ms                                                                                                                      |
| Surface hardness          | Pencil hardness:3H                                                                                                        |
| Total light transmittance | Up to 85%                                                                                                                 |
| Touch life                | >35000000 times                                                                                                           |
| Connectivity              |                                                                                                                           |
| Rear I/O                  | 12V DC in jack*1                                                                                                          |
|                           | USB *1 for touch function                                                                                                 |
|                           | 15PIN D-sub VGA *1                                                                                                        |
|                           | HDMI*1 for option                                                                                                         |
|                           | Audio in*1 for option (built in speaker for option)                                                                       |
| Side key function         | Auto, Menu,Up,Down,Power Swicth                                                                                           |
| Environment               |                                                                                                                           |
| Operating temperature     | 0 to 40 degrees centigrade                                                                                                |
| Storage temperature       | -10 to 60 degrees centigrade                                                                                              |
| Working humidity          | 10%~80% No condensation                                                                                                   |
| Storage humidity          | 10%~90% No condensation                                                                                                   |
| Package                   |                                                                                                                           |
| Package with foam inside  | 570*130*500mm/7.5kg                                                                                                       |
| 5 in 1 carton             | 570*490*500mm/28kg                                                                                                        |
| Accessories               |                                                                                                                           |
| Power adapter             | 110-240V/50-60HZ AC power input ,DC12V/4A output adaptor                                                                  |
| Cable                     | Power cord compatible with USA /EU / UK etc and customized available,USB cable for touch,VGA cable(HDMI cable for option) |
| Touch related             | Touch pen,driver disk                                                                                                     |
| Other                     |                                                                                                                           |
| Certification             | CE,ROHS,CCC,FCC                                                                                                           |















