

# 80MM Thermal Printer with Auto Cutter

(M/N:OCP-80G)

## Features:

- l. Desktop or wall-mounted type for option
- m. Supports multi 1D barcodes and 2D codes printing
- n. 100M Ethernet port, ultra high speed data transmission
- o. Supports black mark detection and order reminding function
- p. Supports printing status monitor and anti-losing order function
- q. Supports 256KB NV Logo storage and 2M big buffer memory

## Specification

Model	OCP-80G
Name	80mm desktop thermal printer with auto cutter
Color	Black
Interface	Serial+USB+Lan/36P parallel port/25P serial +USB/LAN
Power supply	Input AC 100V-240V,50-60Hz,Output DC 24V/2.5A
Cash drawer	DC 24V/1A
Printer head lifespan	150KM
Cutter life	1.5 million cuts
Cutter	Auto cutter
Buffer	Input buffer 2048K NV Flash 256K
Accessories	Data cable,power adaptor,power cord,paper roller,CD,manual
OS supporting	Compatible with iOS/ Android/ Windows/Linux
Safety standards	CE ,FCC,Rohs etc
Printing method	Direct thermal line
Resoluiton	576 Dots/Line or 512 Dots/Line 8dots/mm,203dpi
Printing speed	230mm/s ,260mm/s
Print width	79.5±0.5mm
Line Spacing	3.75 mm Can adjust line spacing by command
Line number	Font A:42 or 48 character /Line Font B:56 or 64 character/Line Simple,traditional Chinese:21 or 24 lines
Printing Command	Compatible with ESC/POS
Barcode	1D barcode: UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128 2D barcode: QRCODE/ only URL interfae support PDF417
Character size	384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm FontB:9*17dots ,1.1(W)*2.1(H)mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Character set	PC347 Standard Europe/Katakana PC850 Multilingual/PC860 Portuguese PC863 Canadian-French/PC865 Nordic West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866 Cyrillic#2/PC852 Latin2/PC858(Latin2)/IranII/Latvian Arabic/PT151 1251
Media	

Paper type	Thermal roll paper
Paper width	79.5±0.5mm
Paper roll diameter	80mm max
Paper Thickness	0.06-0.08mm
<b>Physical</b>	
Dimension	190*147*142.5mm
Weight	2.32kg
Package box	300*220*190 mm
6 in 1 carton	700*340*440mm/15kg
<b>Environment</b>	
Working temperature& humidity	0 to 45 degrees centigrade, 10%~80% No condensation
Storage temperature& humidity	-20 to 60 degrees centigrade , 10%~90% No condensation





