

2015 USB Portable Stocktaking Terminal Industrial PDA

Features:

2015 USB Portable Stocktaking Terminal Industrial PDA

Suitable for overall process of the commodity circulation including receiving, shipping, stocktaking, loss report, replenishment etc;

Support product information download, automatically matches products and show product name after scanned the barcode;

2.8 inches color display, menu with image for easy operation;

2800mA super capacity battery ensures long working time;

Specification:

Performance Characteristics	
Light source	650nm laser
Scan Model	Single line
Scan width & field	220mm/0~250mm□0.33mm□PCS 90%□
Interface	Standard configuration mini USB receiver; RS232 and PS2 optional
Scan rate	48±2 scan/second
Error Rate	1/5,000,000
Working way	triggered or automatic (continuous mode) scanning
Scan angle	Pitch 30°/ Roll 65°/Yaw 55°
Supported barcodes	EAN-8,EAN-13,UPC-A,UPC-E,Code 39,Code 93,Code 128,EAN128,Codabar, Industoal 2of 5,Interleave 2of5,Matrix 2of5, MSI etc.
Indicator	Beeper, LCD display
Physical Characteristics	
Screen	2.8 inch, 10*10 lines; resolution: 320*240
Dimensions	Terminal: 160x68x29mm; Receiver: 52x20x10mm
Material	ABS+ silica
RAM	16M
Color	Black or Grey
Communication Characteristics	
Frequency	433MHZ
Modulation	GFSK
Transmission Distance	Visual straight line distance 300 meters (Max)
Transmission rate	200Kbps
Electric Characteristic	

Battery	Li-Battery□3.7V,2800mAh□	
EMI/RFI:	CE&FCC DOC compliance	
Working Current	50mA	
Environment		
Operation Temperature	0 Degree C~45 Degree C	
Storage Temperature	-20 Degree C ~60 Degree C	
relative humidity	5%~95%□non- condensing□	
ambient brightness	Max 5,000Lux	
Ordering Information		
OCBS-D007	433MHZ Wireless Portable Stocktaking Terminal	
OCBS-D107	USB Cable Portable Stocktaking Terminal	

Product Details:



Relevant documents:

Do you want to know more product information?Please Click here.

[Specification](#)

[User's Manual](#)

[OCBS-D107 receiver driver 64bits](#)

[OCBS-D107 receiver driver 32bits](#)

[OCBS-D107 PC Application](#)

[OCBS-D107 SDK\(DLL2.0\)](#)