

# OCPP-88A-W new wifi pos thermal printer for kitchen

(Model No.: OCPP-88A-W)

## Features:

Unique appearance with reliable mould;  
High Printing Speed up to 300mm/second;  
Auto Cutter ;  
Interface Wifi+USB  
Sound and light alarm supported suitable for kitchen application;  
Support multiple 1D and QR code types printing;  
Support multi international languages;  
SDK for Android available;  
Reliable printer head with 100km life;  
Compatible with EPSON ESC/POS commands.

## Parameters:

|                      |   |
|----------------------|---|
| Printing Method      | Thermal line printing   |
| Printing Character   | 576dots/line (default), 512dots/line;<br>Characters : Simplified Chinese 24x24 point, support 18030 font library, support Taiwan and HK traditional (complex font), ANK characters; |
| Font                 | A: 12*24dots,1.5(W)*3.0(H)mm;<br>B: 9*17dots,1.1(W)*2.1(H)mm<br>Simplified/Traditional : 24*24dots, 3.0(W)*3.0(H)mm   |
| Barcode Type         | JUPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128, QR code   |
| Printing Speed       | 250mm/sec for a single interface ,300mm/sec for Double interface and three interfaces   |
| Interface            | USB, USB+Serial, USB+ LAN, USB+ Serial+ LAN, Wifi+USB, Bluetooth+USB+LAN  |
| Printing Command     | Compatible with EPSON ESC/POS commands  |
| Drivers              | Win9X/ Window XP /Win2000/Win2003/Win Vista/ Win 7/ Win 8/win8.1/Linux, compatible with ESPON, SDK for Android available.   |
| Printing Width       | 79.5±0.5mm( print width 72mm)   |
| Paper Diameter       | 83mm  |
| Paper Thickness      | 0.06-0.08mm   |
| Cutter               | Auto cutter (optional)  |
| Printing Reliability | 100km   |
| Power                | DC24V/2.5A  |
| Temperature          | 0-45 degree C   |
| Contrast Humidity    | 10-80%  |
| External Dimension   | 190*145*145(mm)   |
| Weight               | 1.60kg  |

|                      | P/N           | Description                              |
|----------------------|---------------|--|
| Ordering information | OCPP-88A-U    | USB port, with auto cutter               |
|                      | OCPP-88A-UR   | USB+Serial port, with auto cutter        |
|                      | OCPP-88A-UL   | USB+Lan port, with auto cutter           |
|                      | OCPP-88A-URL  | USB+Serial+Lan port, with auto cutter    |
|                      | OCPP-88A-W    | Wifi+USB port, with auto cutter          |
|                      | OCPP-88A-BUL  | Bluetooth+USB+LAN, with auto-cutter      |
|                      | OCPP-88A-U0   | USB port, without auto cutter            |
|                      | OCPP-88A-UR0  | USB+Serial port, without auto cutter     |
|                      | OCPP-88A-UL0  | USB+Lan port, without auto cutter        |
|                      | OCPP-88A-URL0 | USB+Serial+Lan port, without auto cutter |
|                      | OCPP-88A-W0   | Wifi+USB port, without auto cutter       |
|                      | OCPP-88A-BUL0 | Bluetooth+USB+LAN, without auto-cutter   |

