2016 Andriod touch screen pos terminal with printer made in China

(M/N:POS-T8)

Features:

- 1. Android 4.4 operation system.
- 2.Adopts Qualcomm quad-core 1.2GHz processor.
- 3.4.0 inches IPS capacitive touch screen.
- 4. Safety and reliable design
- 5. Passed Unionpay Pboc L1 & amp; L2; passed PIN input safety certification.
- 6. Unionpay direct connect POS network access.
- 7. Support Pirnting Receipt and Barcode reading
- 8. Supports magnetic stripe card, IC card, contactless card.

Specifications: System Parameters CPU Qualcomm quad-core 1.2GHz OS Android 4.4 RAM / ROM RAM / ROM Bisplay At 0 inch capacitive, multi touch; 480 * 800, IPS display Keypad Reypad	
Android 4.4 RAM / ROM ROM 4GB eMMC; RAM 512MB / 1GB DDR2; support external micro SD card, 32 GB at most Display 4.0 inch capacitive, multi touch; 480 * 800, IPS display Xeypad Battery Lithium polymer battery, 4000mAh Functional Configuration Camera Rear Camera 5M AF (support flashlight), Front Camera 0.3N angle Printer Built-in 2 inches thermal printer Navigation Built-in GPS, support AGPS Indicator Light System indicator light, POS indicator light Audios Built-in speaker, buzzer, microphone, vibrator Sensors Gravity sensor POS Sound Wave Payment Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 1 SAM Solt, ISO / IEC 14443 Type A / B, qPBOC SAM Card Cipher Keyboard Network Parameters Network Type WCDMA / GSM WCDMA 2100MHz	
Android 4.4 RAM / ROM ROM 4GB eMMC; RAM 512MB / 1GB DDR2; support external micro SD card, 32 GB at most Display 4.0 inch capacitive, multi touch; 480 * 800, IPS display X Eypad	
support external micro SD card, 32 GB at most 4.0 inch capacitive, multi touch; 480 * 800, IPS display 3 Touch System Keys, 15 physical keys (include Power key, 6 key, POS Cipher key and Command key) Battery Lithium polymer battery, 4000mAh Functional Configuration Camera Rear Camera 5M AF (support flashlight), Front Camera 0.3N angle Printer Built-in 2 inches thermal printer Navigation Built-in GPS, support AGPS Indicator Light System indicator light, POS indicator light Audios Built-in speaker, buzzer, microphone, vibrator Sensors Gravity sensor POS Sound Wave Payment Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 1 SAM Solt, ISO7816 Cipher Keyboard Network Parameters Network Type WCDMA / GSM WCDMA 2100MHz	
Support external micro SD card, 32 GB at most 4.0 inch capacitive, multi touch; 480 * 800, IPS display 3 Touch System Keys, 15 physical keys (include Power key, 6 key, POS Cipher key and Command key) Battery Lithium polymer battery, 4000mAh Functional Configuration Camera Rear Camera 5M AF (support flashlight), Front Camera 0.3N angle Printer Built-in 2 inches thermal printer Navigation Built-in GPS, support AGPS Indicator Light System indicator light, POS indicator light Audios Built-in speaker, buzzer, microphone, vibrator Sensors Gravity sensor POS Sound Wave Payment Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 13.56MHz, ISO / IEC 14443 Type A / B, qPBOC SAM Card 1 SAM Solt, ISO7816 Built-in keypad Network Parameters Network Type WCDMA / GSM Natwork Spectrum WCDMA 2100MHz	
Keypad 3 Touch System Keys, 15 physical keys (include Power key, 6 key, POS Cipher key and Command key) Battery Lithium polymer battery, 4000mAh Functional Configuration Camera Rear Camera 5M AF (support flashlight), Front Camera 0.3N angle Printer Built-in 2 inches thermal printer Navigation Built-in GPS, support AGPS Indicator Light System indicator light, POS indicator light Audios Built-in speaker, buzzer, microphone, vibrator Sensors Gravity sensor POS Sound Wave Payment Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 1 SAM Solt, ISO7816 Cipher Keyboard Network Parameters Network Type WCDMA / GSM Natwork Spectrum WCDMA 2100MHz	
Keypad 3 Touch System Keys, 15 physical keys (include Power key, 0 key, POS Cipher key and Command key) Battery Lithium polymer battery, 4000mAh Functional Configuration Camera Rear Camera 5M AF (support flashlight), Front Camera 0.3M angle Printer Built-in 2 inches thermal printer Navigation Built-in GPS, support AGPS Indicator Light System indicator light, POS indicator light Audios Built-in speaker, buzzer, microphone, vibrator Sensors Gravity sensor POS Sound Wave Payment Support Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 1 SAM Solt, ISO7816 Cipher Keyboard Built-in keypad Network Parameters Network Type WCDMA / GSM Natwork Spectrum WCDMA 2100MHz	
Battery Lithium polymer battery, 4000mAh Functional Configuration Camera Rear Camera 5M AF (support flashlight), Front Camera 0.3N angle Printer Built-in 2 inches thermal printer Navigation Built-in GPS, support AGPS Indicator Light System indicator light, POS indicator light Audios Built-in speaker, buzzer, microphone, vibrator Sensors Gravity sensor POS Sound Wave Payment Support Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 13.56MHz, ISO / IEC 14443 Type A / B, qPBOC SAM Card 1 SAM Solt, ISO7816 Cipher Keyboard Built-in keypad Network Parameters Network Spectrum WCDMA / GSM Notwork Spectrum WCDMA 2100MHz	ustom
Functional Configuration Camera Rear Camera 5M AF (support flashlight), Front Camera 0.3N angle Printer Built-in 2 inches thermal printer Navigation Built-in GPS, support AGPS Indicator Light Audios Built-in speaker, buzzer, microphone, vibrator Sensors Gravity sensor POS Sound Wave Payment Magnetic Strip Card I riple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 1 SAM Solt, ISO7816 Cipher Keyboard Network Parameters Network Type WCDMA / GSM WCDMA 2100MHz	
Rear Camera 5M AF (support flashlight), Front Camera 0.3N angle Printer Built-in 2 inches thermal printer Navigation Built-in GPS, support AGPS Indicator Light System indicator light, POS indicator light Audios Built-in speaker, buzzer, microphone, vibrator Sensors Gravity sensor POS Sound Wave Payment Support Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 13.56MHz, ISO / IEC 14443 Type A / B, qPBOC SAM Card 1 SAM Solt, ISO7816 Cipher Keyboard Built-in keypad Network Parameters Network Type WCDMA / GSM Network Spectrum WCDMA 2100MHz	
Printer Navigation Built-in QPS, support AGPS Indicator Light System indicator light, POS indicator light Audios Built-in speaker, buzzer, microphone, vibrator Sensors Gravity sensor POS Sound Wave Payment Magnetic Strip Card Iriple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 13.56MHz, ISO / IEC 14443 Type A / B, qPBOC SAM Card 1 SAM Solt, ISO7816 Cipher Keyboard Network Parameters Network Type WCDMA / GSM WCDMA 2100MHz	wide
Navigation Built-in GPS, support AGPS Indicator Light System indicator light, POS indicator light Audios Built-in speaker, buzzer, microphone, vibrator Sensors Gravity sensor POS Sound Wave Payment Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card I Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card I SAM Solt, ISO / IEC 14443 Type A / B, qPBOC SAM Card I SAM Solt, ISO7816 Cipher Keyboard Network Parameters Network Type WCDMA / GSM WCDMA 2100MHz	
Indicator Light Audios Built-in speaker, buzzer, microphone, vibrator Sensors POS Sound Wave Payment Magnetic Strip Card IC Card Contactless card Sam Card Cipher Keyboard Network Spectrum System indicator light, POS indicator light Built-in speaker, buzzer, microphone, vibrator Buipt-in speaker, buzzer, microphone, vibrator Buzzer, buzzer, microphone, vibrator Buzzer, buzzer, microphone, vibrato	
Audios Built-in speaker, buzzer, microphone, vibrator Gravity sensor POS Sound Wave Payment Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 13.56MHz, ISO / IEC 14443 Type A / B, qPBOC SAM Card 1 SAM Solt, ISO7816 Cipher Keyboard Network Parameters Network Type WCDMA / GSM WCDMA 2100MHz	
Sensors POS Sound Wave Payment Magnetic Strip Card ITriple track MSR, bi-directional swiping ISO7811, 7812 IC Card I Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card I SAM Solt, ISO / IEC 14443 Type A / B, qPBOC SAM Card I SAM Solt, ISO7816 Cipher Keyboard Network Parameters Network Type WCDMA / GSM WCDMA 2100MHz	
Sound Wave Payment Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 13.56MHz, ISO / IEC 14443 Type A / B, qPBOC SAM Card 1 SAM Solt, ISO7816 Cipher Keyboard Built-in keypad Network Parameters Network Type WCDMA / GSM WCDMA 2100MHz	
Magnetic Strip Card Triple track MSR, bi-directional swiping ISO7811, 7812 IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 13.56MHz, ISO / IEC 14443 Type A / B, qPBOC SAM Card 1 SAM Solt, ISO7816 Cipher Keyboard Built-in keypad Network Parameters Network Type WCDMA / GSM WCDMA 2100MHz	
IC Card 1 Solt, Support 1.8V / 3V / 5V, ISO7816, PBOC and EMV Contactless card 13.56MHz, ISO / IEC 14443 Type A / B, qPBOC SAM Card 1 SAM Solt, ISO7816 Cipher Keyboard Built-in keypad Network Parameters Network Type WCDMA / GSM WCDMA 2100MHz	
Contactless card 13.56MHz, ISO / IEC 14443 Type A / B, qPBOC SAM Card 1 SAM Solt, ISO7816 Cipher Keyboard Built-in keypad Network Parameters Network Type WCDMA / GSM Network Spectrum WCDMA 2100MHz	
SAM Card 1 SAM Solt, ISO7816 Cipher Keyboard Built-in keypad Network Parameters Network Type WCDMA / GSM Network Spectrum WCDMA 2100MHz	
Cipher Keyboard Built-in keypad Network Parameters Network Type WCDMA / GSM Network Spectrum WCDMA 2100MHz	
Network Parameters Network Type WCDMA / GSM Network Spectrum WCDMA 2100MHz	
Network Type WCDMA / GSM WCDMA 2100MHz	
Network Spectrum WCDMA 2100MHz	
Matwork Spactrum	
GSM / GPRS / EDGE 850/900/1800 / 1900MHz	
WLAN 802.11 a / b / g / n Built-in Antenna	
Voice / Data Service Support	
WPAN Bluetooth V4.0 + EDR	
External Interface	
USB Interface Micro USB2.0, support USB OTG	

Charger Jack	DC JACK
Power Supply Jack	Pogo Pin, 5V - 500mA
Communication	USB, RS232
Physical Parameters	
Dimensions	205mm H * 82mm / 67mm W * 33mm D
Weight	500g (battery included)
Operating Temp	-20 ° C ~ 60 ° C
Storage Temp	-40 ° C ~ 80 ° C
Humidity	10% ~ 90% RH non-condensing
Drop Test	1.0-meter drop protection
Roller Drop Test	500 times
ESD protection	± 8KV contact discharge; ± 15KV air discharge
Development Environment	
System Environment	Android 4.4 / SP-UI
Development Environment	SDK
Management Software	PC management suite / MDM

Power adaptor for option:

Europe, British, America, Australia, Asia etc.

Production capacity and lead time:

We have strong production capacity;. We can produce thousand of printers and barcode scanners per day Normally, our lead time between 1-5 days.

Shipping method:

Air, Sea, Express (DHL, FedEx, UPS, EMS, TNT and so on)

Warranty:

12 + 1 months of shipment normally. Some designated models can have as long as 24 months warranty. Spare parts can be provided for mass order.

Payment term:

T / T in advance, Western Union, PayPal, Escrow, L / C, Cash, etc

About OCOM

OCOM is a leading One-stop POS and Auto-ID Related Products Supplier, which is qualified by Global Fortune 500 company. We have Top 1% level Trade Assurance guarantee. 8 Years OEM / ODM Experience. We were serving more than 1300 customers over 133 countries, 40 of them are the biggest distributors in their territory. The main market in Europe, Australia, and fast growing South America and Africa. The customer list including famous Unilever, O2, Equicom ... We have CE, FCC and other required certifications.

Together we quest for the best.

Contact US

Address: 4 / F, Block 10, Zhongxing Industrial Park, Chuangye Road,

Nanshan District, Shenzhen 518054, China;

Website: www.ocominc.com, www.possolution.com.cn

Tel: +86.755.86053207 ext 800; Fax: +86.755.86053207 ext 868.