2016 China hot selling mini bluetooth thermal receipt printer for iphone

(Model:OCPP-M06)

This mini printer with model number OCPP-M06 is aAndroid (or IOS+ Android), Window, Linux, JAVA compatible battery powered 58mm portable mobile thermal pos printer which combines USB,RS-232 Serial and Bluetooth (optional) communication ways together. This printer could be powered by rechargeablebattery, power adapter, or car charger (depending on specified models). Special model can connect with 8 smart devices for printing at same time. We have CE, FCC and other required certifications.

Features:

- 1. Mini size suitable for portable application;
- 2. Windows, Java, Linux, Android (or Android+IOS) operation system supported;
- 3. Bluetooth, USB and RS232 communication supported;
- 4. SDK for Android available;
- 5. 1D, 2D barcode (QR code), and image printing supported;
- 6. Can change the printer name, password, baud rate online;
- 7. One printer can connected with up to 8 smart devices (7 Android, one Apple device) visa blue tooth;
- 8. Low power consumption and large capacity Lithiumbattery (1500mAh), 4~5 days standby;
- 9. Powered by rechargeablebattery, power adapter, or car charger (specified models)
- 10. Higher print speed 90mm/sec;
- 11. 100km thermal printer head life;
- 12. Multiple languages supported;
- 13. ESC/POS command setcompatible;

Specification:

Overall Dimension ($W \times D \times H$)	105×75×45mm
Weight	134g
Color	Black
Print method	Thermal line printing
Print commands	ESC/POS compatible command set
Effective print width	48mm
Print speed	Up to 90mm/sec
Resolution	8 dots/mm(203dpi)
Print font	12x24/ 24x24

Column capacity		32 columns/ 16columns
Character size		1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH)
Paper dimensions		58.0±0.1mm x diameter 40.0mm
Paper thickness		0.06 to 0.08mm
Character set		Alphanumeric/ Chinese Kanji
Interface		USB, RS-232□Bluetooth (optional)
Flash		256KB
Power Adapter		9V DC/2A
Battery Power		7.4V DC/ 1500mAh; battery can stay by for 4-5 days, when it is full
		power, it can print 120-150m paper
Other features		Paper detection, manual shut down
Working conditions		Temperature:-10~50 degC,Humidity:10%□90%
Storage conditions		Temperature:-20~70 degC, Humidity:5%□95%
Device name		Can be customized, letter and digital for option, at max 30 ASCII
		characters.
IPaccinora		Enter default pairing code "1234", it can be customized or change by
		customer itself. At max 6 digitals.
Power plug dimension		3.5*1.1mm
Ordering information	OCPP-M06-BB	Android, USB+COM+Bluetooth, Battery.
	OCPP-M06-BB-AI	Android+IOS, USB+COM+Bluetooth, Battery.
		Android, USB+COM+Bluetooth, without Battery;
	OCPP-M06-U	Mini printer, Android, USB+COM, without Battery.
	I II PP-MINN-KK-AA	Android+IOS, USB+COM+Bluetooth, Battery, 7 android +1 apple
		devices supported