

2016 New product 2d barcode scanner

(M/N:OCBS-2008)

Feature:

High performance imaging technology;
 Omni-directional scanning, easy to scan;
 Can read the barcode on the screen and color barcode;
 4mil excellent scanning accuracy ;
 Multi special function setting supported;
 SDK/API Available;
 Multi interfaces optional;
 Stand for option.

Performance Characteristics

Function		
Light source	White LED	
Beep	Supported	
Stand	Optional	
Indicator	Green LED, beep	
Scan performance		
Sensor	CMOS	
Resolution	640*480,256 gray levels	
Maximum decoding speed	13mil UPC 40cm/s	
Reading angle	horizontally 50 deg; vertically 20 Deg	
Precision	≥4mil	
Decode capability	1D	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128 (GS1-128), ISBT 128, Code93, Code 11 (USD-8), MSI/Plessey
	2D	PDF417, MicroPDF417, QR Code, DataMatrix, Han Xin Code, Aztec Code, GS1 Composite
Depth of field	Code 39(5mil) □50mm~120mm Code 39(10mil) □25mm~250mm UPC/EAN (13mil) □20mm~320mm Data Matrix(7.5mil) □63mm~150mm PDF417(6.6mil) □62mm~145mm	
Sensitivity	Inclination ±45° @0°Roll and 0°Skew Rotation ±30° @0°Pitch and 0°Skew Deflection ±45° @0°Roll and 0°Skew	
Electrical		
Interface	USB,USB COM(virtual serial port)	
Input Voltage	3.3v~5v DC	
Standard Power	2.0w (400mA)	
Max Power	2.5w (450mA)	
DC adapter	Max 5.5V 1A	

LED CLASS	Class I
EMC Test	FCC part15,IEC60825-1,EN55022 Class B
User Environment	
Operate Temperature	-20 deg C ~ +60 deg C (-4 Deg F to 144 deg F)
Storage Temperature	-30 deg C ~ +70 Deg C (-22 Deg F to 158 deg F)
Humidity	5% - 95%(non- condensation)
Drop resistance:	1.5m (5.0ft) drops to concrete
IP class	IP54
Light intensity	Working: sun lights, fluorescent lights
Physical	
Dimensions	156*68*83mm
Weight	195 g (without stand)
Package dimension	48*36*47CM (20pcs with stand 13.5KG)
	48*39*52CM (30pcs without stand 15KG)

