

2d Omini Auto-sense barcode scanner ,Ominidirectional barcode scanner

Features:

auto-sense scanner,Ominidirectional barcode scanner,2d Omini barcode scanner

Can read the image acquisition and decoding

Omni-directional scanning,easy to scan

Desktop flatbed & Concise design

With steady stand & reliable scanner module

High speed image acquisition and decoding

Parameters:

auto-sense scanner,Ominidirectional barcode scanner,2d Omini barcode scanner

Performance parameters	
Light source	White LED
Buzzer	Seven tones or silent
Lamp	White
System interface	KBW, RS232,USB
Physical parameters	
Volume(Lx W x H)	Product size 78 mm x 75 mm x 141mm (3.2" x 3.3" x 5.9"),
Weight	Product size180 g (12 oz)
Electrical parameters	
Input voltage	5.5 VDC \pm 0.25 V
Work power	2.0 W (430 mA @ 5 V)
Standby power	0.5 W (100 mA @ 5 V)
Environmental parameter	
Operating temperature	0° C - 40° C
Storage Temperature	-40°C -60°C
Humidity	0% to 95% relative humidity (no condensation)
Antiknock characteristic	Withstand 1.5 meters high drop from concrete floor.
Dust-proof	Seal to prevent air dust particle erosion.
Scanning parameters	
Scanning mode	Omni directional (640X480)
Highest Reflectivity	Max 20% reflectivity can be read
Scanning Angle	70°, 75°

