## 3 inch 1D/2D Bar code Printing Pocket Bill Thermal Receipt Printer

(M/N:OCPP-M085)

### Products Features ☐

- 1. Business style design, more fashion
- 2. Support 1.D,2.D bar code printing
- 3. While compatible with Windows, Linux, Android and IOS systems
- 4. With 2500mAh rechargeable lithium polymer battery, super battery lasting time, with smart power saving and power consumption control functions, to ensure longer print time
- 5. Support USB+COM +Bluetooth or USB+COM+Bluetooth+WIFI,
- 6. Special power remaining indicator light, to control the printer power at any time
- 7. Support sound and light reminder when lack of paper or printing abnormal
- 8. Anti fall of 1.5M cement floor

## Application:

Warehousing, transportation, logistics, supermarket, tobacco, hydropower reading, mobile government affairs, mobile police, postal and other industries

#### Parameters ☐

Printing Method. Thermal Line Effective Printing Printing Width Resolution 376 dots/line[Bdots/mmt][203dpt] Printing Speed 30mm/S Interface USB (standard USB2.0 communication protocol, support Windows, Linux, Android, IOS) Blutooth (Bluebooth 2.0, Bluetooth 3.0 4.0, support Android, IOS) WIFI (1,2 4GHZ, ATA, AP, ATA+AP mode) Direction (Line spacing) 3.75mm(Can adjust line spacing by command] Line No. Fort A-48 character / Line Fort B-64 character /			
Effective Printing   2mm   1 mm   2			Parameter
Worth			
Price   Section   Description   Descriptio		Width	
Interface   Sil (Landard 1982 20 communication protocol, upport Windows, Linux, Android, US)			
Proceedings		Priting Speed	90mm/S
Line No. For A-84 Character Jule For Both Scharacter Jule For Both Scha			Bluetooth (Bluetooth3.0, Bluetooth3.0+4.0,support Android, IOS)
For the Set Character   Simple proteined Characters   The standard CB18003 angilled of proteined standard CB18003 angilled of proteined standard CB18003 angilled of proteined common			
Character Size			Font B:64 character/Line
Fort B[].1.V2.Timm[9:17 dots] Simplified/Tradiosal[3] 0.93 (Jamel/Belf/Tradiosal[3] 0.93 (Jamel/Belf/Belf/Tradiosal[3] 0.93 (Jamel/Belf/Belf/Tradiosal[3] 0.93 (Jamel/Belf/Belf/Tradiosal[3] 0.93 (Jamel/Belf/Belf/Belf/Belf/Belf/Belf/Belf/Be		Character	The standard GB18030 simplified / traditional Chinese characters library
Extended character set		Character Size	ANK Character[Fort At] 1-5/3.0mm[]12×24 dots] Fort B[11+2.7_Imm[9x+7 dots] [smillipel[7-aditions]]3.0×3.0mm[24×24dots]
Bar code Arracter Graphics Graphics of printing Smart power Swang Available speed Support Supp		Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/Iranl/(Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThalVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
smart power saving support saving support saving printing support saving support saving support saving support saving support support saving support s	Bar code character		CODABAR/CODE93/CODE128 2D.Bar code]QR/CODE
Saving Saving Power saving printing Power Saving Printing Support Saving Power Saving Printing Support	Graphics printing	Graphics printing	Supports bitmap download and print
Power swing printing   Mode   Consumption   Support	Power saving Mode		Support
Dection   Sensor   Lack of paper detection		Variable speed printing	Support
Dection Sensor Ack of paper detection  Indicator Power Display Support Lack of paper Sup		Consumption	Support
Power Display   Support		Dormancy	Support
Charge Indicator   Support	Dection	Sensor	Lack of paper detection
Eack of paper   Support	Indicator	Power Display	Support
Rep	Paper	Charge Indicator	Support
Paper   Type		Lack of paper	Support
Width		Веер	Lack of paper, printing abnormal alarm
Thickness   So 1.2mm   Diameter   \$40mm   Feed   \$240mm   \$240mm		Type	Thermal
Diameter		Width	79.5±0.5mm
Diameter			
Feed			
Print commands         CSC/POS commands         ESC/POS commands         ESC/POS commands           Power Capacity         Type         Rechargeable Lithium polymer battery           Capacity         250mAN/7 AV. can be charged more than 800 times sustainable printing 150 meters or 4 hours under normal use Charger         9.074           Duffer Input         MXP Rash         40KB           Physical Vestures         VPI rash Dimension         114*103*50(MM)           Environment Storage         114*103*50(MM)           Reliability         Frempl_10 - 50°C (PHumidity[10 ~ 90%]No Dev]           Reliability         Frempl_10 - 50°C (PHumidity[11 ~ 90%]No Dev]			
Capacity   250mAh/7 AV, can be charged more than 800 times   sustainable printing 150 meters or 4 hours under normal use   Charger   9.0VZA			
Capacity   250mAh/7 AV, can be charged more than 800 times   sustainable printing 150 meters or 4 hours under normal use   Charger   9.0VZA		Type	Rechargeable Lithium polymer battery
Charger   9.0//2A			2500mAN/7.4V, can be charged more than 800 times
Suffer		Charger	
NV Flash   40KB	Buffer		
Physical   Reliability   2856			
20			
Storage Temp[-10 ~ 50°C []Humidity[10 ~ 90%[]No Dew[]  Reliability Print head life 50KM[Printing Densitys12.5]			
Reliability Print head life 50KM[Printing Density≤12.5]	L		
	Poliability		
	,		
	Dourmare	Dilvei	Participal Constitut, White Land Constitution and Constit



# OCPP-M085







# OCPP-M085











# OCPP-M085







