

sticker printer,barcode label printer,label thermal printer

3 inch label thermal printer, sticker printer (OCBP-005)

Features:

sticker printer,barcode label printer,label thermal printer

- Label paper auto position;
- Labels peel off, tear off automatically;
- Adjust the printer head pressure;
- Compatible with plenty of label software;
- BMP, PCX, BAC images download store;
- Support Serial, USB, LAN together;
- Support PDF417, QR CODE, DOTMATRIX;

Parameter:

sticker printer,barcode label printer,label thermal printer

Printer Model	OCBP-005
Resolution	203 dpi (8 dots / mm)
Printing Method	Direct thermal
Head temperature sensor	Varistors thermal
Sensor head position	Microswitch
Detection paper	Photoelectric
Print speed	127 mm / sec (max)? 50.8 mm / sec (min)
Print width	16 mm to 82 mm
Average	Media Type: roll, stickers, labels times, and so on. Average diameter Inside diameter: 25 mm; Diameter: 80 mm
Internal font	Font FONT 0 8? font commonly used one byte
Zoom & amp; amp; amp?	1-10 times improvement in multiple directions; 0 °, 90 °, 180 °, 270 °, 360 °
Rotating	
Outside the paper type	Rip & amp; amp; amp? peeling
Memory cards	2MB FLASH ROM, 2 MB DRAM
Image	Monochrome PCX, BMP image files can be loaded in Flash, DRAM
Barcode	CODE128, EAN 128, ITF, Code39, Code93, EAN13, EAN13 2, 5 EAN13, EAN8, EAN8 2, 5 EAN8, Codabar, POSTNET, UPC-A, UPCA 2, UPCA 5, UPC-E, UPCE 2, UPCE 5, CPost, MSI, MSIC, PLESSEY, ITF14, EAN14, PDF417, QR Code, DATMATRIX
Interconnection	USB + RS232 + LAN or USB
Power	Login: 24VDC, 2.5A
Environment	Operating Temperature: 5 ° C to 45 ° C Storage temperature: -40 ° C to 55 ° C Operating Humidity: 20% ~ 80%, non-condensing, free air Storage humidity: & amp; amp; lt? = 93% (40 ° C), no condensation, free air
Size	Format: D220mm H148mm * W150mm *

Product Details:

sticker printer,barcode label printer,label thermal printer

