

# 3 inch thermal POS ticket printer (OCP-80E)

**Keywords:**  
**thermal printer,**  
**pos printer,**  
**ticket printer.**

## Features:

- Desktop or wall-mounted type for option.
- Supports multi 1D barcodes and 2D codes printing.
- 100M Ethernet port, ultra high speed data transmission.
- Supports 256KB NV Logo storage and 2M big buffer memory.
- Supports black mark detection and order reminding function, compatible with OPOS driver.
- Supports printing status monitor and anti-losing order function.

## specification:

Printing method:	Direct thermal
Printing speed:	230mm/s/260mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line/512 Dots/line
Line's pacing :	3.75mm/Adjustable by commands
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+Lan/36P parallel port/25P serial +USB/LAN
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V/50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0~45) humidity(10~80%) Non- condense
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10~60°C); Humidity(10~90%)
Character size:	ANK/FontA:1.5*3.0mm/ FontB:1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA/EAN13/JAN8/EAN8/CODE39/ITF /CODE93/CODE128 QRCode
Characters:	PC347/Standard Europe/Katakana/PC850/Multilingual/PC860/Portuguese/PC863/Canadian-French/PC865/Nordic/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/Cyrillic#2/PC852/Latin2/PC858/IranII/Latvian/Arabic/PT151/1251



