

3inch with Autocutter POS Thermal Receipt Printer

OCPP-80E

Printing method:	Direct thermal
Printing speed:	200mm/s(260mm/s for 3 interface)
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line(512 Dots/line)
Line's pacing :	3.75mm(Adjustable by commands)
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+Lan/36P parallel port/25P serial +USB/LAN
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V(50~60Hz)
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0(45) humidity(10(80%) Non- condense
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10(60°C); Humidity(10(90%)
Character size:	ANK(FontA:1.5*3.0mm/ FontB(1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA(EAN13(JAN8(EAN8/CODE39/ITF /CODE93/CODE128 QRCode
Characters:	PC347(Standard Europe(Katakana(PC850(Multilingual(PC860(Portuguese(PC863(Canadian- French(PC865(Nordic(West Europe(Greek(Hebrew(East Europe(Iran(WPC1252(PC866 (Cyrillic#2(PC852(Latin2 (PC858(IranII(Latvian(Arabic(PT151(1251



Relevant documents:

[*Specification](#)

[*IP Address Configure Manual](#)

[*Instruction Manual](#)

[*Driver for all windows system](#)

[*Driver for Linux](#)

[*Printer Parameters Setting Tools](#)

[*CD Files](#)