

58mm POS thermal receipt printer (OCP-586)

Specification:

| | |
|---------------------|---|
| Printing Method | Direct thermal |
| Print Density | 384dots / line (203DPI) |
| Character Size | 384dots / line, ANK character, Font: A: 12 * 24dots, 1.5 (W) * 3.0 (H) mm Simplified / Traditional: 24 * 24dots, 3.0 (W) * 3.0 (H) mm |
| Barcode Type | JAN13(EAN13)JAN8(EAN8)CODE39 QR CODE (Optional function) |
| Printing Command | Compatible with EPSON ESC / POS |
| Language | OEM437 / Katakana / OEM850 / OEM860 / OEM863 / OEM865 / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / OEM866 / OEM852 / OEM858 / IranII / Latvian / Arabic / PT151,1251 / OEM747 / WPC1257 / Vietnam / OEM864 / Hebrew / WPC1255 / Thai |
| Printing Speed | 90mm / sec |
| Paper Width | 57.5 ± 0.5mm |
| Paper Thickness | 0.06-0.08mm |
| MCBF (life) | 50km |
| Dimension | 190 * 132 * 119mm |
| Gross Weight | 1.2KG |
| Auto Cutter | manual cutter |
| Sensor | Paper Near End Sensor, Paper End Sensor, Cover open sensor |
| Roll Paper | Φ75mm |
| Interface | RS-232C, Parallel, USB, LAN |
| Driver | Win 9X, Win 2000, Win 2003, Win XP, Win Vista, Win 7 Win8 Win10 compatible with ESPON |
| Printer Supply | DC12V / 3A |
| Cash Drawer Control | DC12V / 1A |
| Working Temperature | 0-45°C, Humidity: 10-80% |
| Saving Temperature | -10-60°C, Humidity: 10-90% |

Product Details:

