58mm thermal head receipt POS printer

(OCPP-58E)



Product Introduction:

OCPP-58E is a well-

designed economic printer for common thermal bill printing ,this mold is with solid material, Exquisit e workmanship. Transparent cover design, simple and fashion, easy for users to know the paper rolls' Using status, OCPP-58E adopt built-

in power supply,not only can save space,but also easy for users to configure and use the printers.It's a very good choice for economical printing.

pos printer, thermal head printer, 58mm thermal printer

- •Simple and fashion, With solid material, exquisite workmanship.
- Easy paper install structure, simple and convenient to operate
- •Built-in power supply design, to save space and more convenient to configure;
- •Transparent cover design, the user can know the paper roll's using status anytime;
- •Support GB18030 big font, easy to print uncommon characters
- •Support multi language print, suitable for users all over the world;
- •Support download and print LOGO&graphics;
- •Support Windows, Linux, Android and IOS system printing

Application Area

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters □

F-		
Items		Parameters
Print parameters	Printing Method	Thermal Line
	Printing Width	48MM
		384dots/Line[Bdots/mm[]203dpi[]
	Printing Speed	90mm/Second
		USB[IUSB+Bluetooth
		3.75 mm[Can adjust line spacing by command[]
		Font A32 character/Line Font B42 character/Line Simple, traditional Chinese-16 lines
	Character	Standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANK-haracter[Fort At]1.5-3.0mm[]12×24dots[] Fort B[]1.4.2 [Imp[8/17408] Simp[ined/Traditional Chinese[3.0×3.0mm[24×24 dots]]
Bar code Character	Extended character set	PC437/Katakana/PC850/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/fran/WPC1252/PC866/PC852/PC852/PC852/PC852/PC352/PC352/PC352/PC866/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian/)(PC1001)/(PC151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	UPC-AUTC-E/ANT-ISCANT SIJ/ANS(EANS)/CODES9/ITF/ CODABAR/CODES9/GODE128
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Type	Thermal Roll
	Width	57.5±0.5mm
	Diameter	s60mm
	Feed Method	Easy feed(Clameshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input(IA_10W-240V_50-60Hz Output(ID_12V/AA
	Casher Drawer output	DC 12V/IA
Buffer	Input Buffer	4K
	NV Flash	40K

physical characteristics Weight		590g
	Dimension	185*130*112(MM)
Environment	Working	Temp[5 ~ 45°C] Humidity[10 ~ 80%
	Storage	Temp[]:10 ~ 50°C []Humidity[]10 ~ 90%[]No dew[]
Reliability parameter	Print Head Life	50KM∏print density≤12.5∏