

80mm Bluetooth Thermal Receipt Ticket Printer for POS System

□Model NO.: OCPP-80K□



Features:

Support 8 kinds abundant interface combination

Supports multi 1D barcode and QR code printing.

Support printer status monitoring function

Support printing queuing ticket function

100M Ethernet port, ultra high speed data transmission.

256KB NV Logo storage and 256kb big buffer memory.

48to80mm adjustable Paper separator for optional

Compatible with OPOS/JPOS driver.

100KM long life printer head

Technical parameters□

Print Method	Direct Thermal
Command	ESC/POS
Resolution	576dots/line or 512dots/line

Printing Width	Max=72mm	
Paper Type	Thermal Receipt Paper	
Interface	USB/UR/UL/URL/U+BT/ U+WIFI/URL+BT/URL+WIFI	
Print Speed	200mm/s (U/UR) 230mm/s (UL) 260mm/s (U+BT/ U+WIFI/ URL/ URL+BT/ URL+WIFI)	
Paper Width	48mm/52mm/56mm/64mm/68mm/76mm/80mm	
Paper Thickness	0.06~0.08mm	
Roll Dia	Max. Ø 83 mm	
Paper Cut	Manual tear and Auto-cutter	
Input buffer	256kbytes	
NV Flash	256kbytes	
Font Size	font A:12*24(standard), font B:9*17	
Chinese	GB18030,BIG5 24x24dots	
Japanese/Korea	Support	
User-defined language	PC347(Standard Europe),Katakana,PC850(Multilingual),PC860(Portuguese),PC863(Canadian-French),PC865(Nordic),West Europe,Greek,Hebrew,East Europe,Iran,WPC1252,PC866(Cyrillic#2),PC852(Latin2),PC858,IranII,Latvian,Arabic,PT151(1251) ect.	
1D	UPC-A/UPC-E/JAN13□EAN13□JAN8□EAN8□/CODE39/ITF/CODABAR/CODE93/CODE128	
2D	QR code (Single USB or UR solution no QR code function)	
Printing head life	100 KM	
Cutter life	1million	
Paper separator	Optional	
Sensors	Paper out, cover open, cutter jam,paper jam and black mark detection(Optional)	
Input	AC 100V-240V 50/60HZ	
Output	DC 24V/2.5A	
Working Condition	0°C~45°C, 10%~80%RH	
Storage Condition	-10°C-60°C,10%~90%RH	
Accessories	Data cable,power adaptor,power code,paper roller,CD>manual, (standard) Paper separator(option)	
Dimensions	196(D)x145(W)x135(H)mm	
Net weight	1.14kg	
Gross weight	1.5kg	
Individual box	Dimension 30X19X18cm(LXWXH□	1unit/carton
Master carton	Dimension 62X36X52cm(LXWXH□	12units/carton
Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS	
SDK	Android, IOS	



OCPP-80K





OCPP-80K





OCPP-80K





OCPP-80K







OCPP-80K

