

80 mm MiniPortable Thermal Reception Printer (M/N: ocpp-M085)



Products Characteristics

- Business style design, More fashion
- 1. d support, 2. D barcode Printing
- While being compatible with Windows, Linux, Android and iOS systems
- with rechargeable 2500mah Lithium polymer battery, super battery life, with intelligent power Economy and Power Consumption control functions to ensure a longer printing time
- USB support, com, Bluetooth, WiFi, USB + Bluetooth (v2.0), USB + bluetooth (v3.0 + v4.0)
- Special power remaining Light, to control the power of the printer at any time
- Sound and light support Reminder when the lack of paper or abnormal printing
- Anti drop of 1.5 m of cement Floor

Application:

Storage, transportation, Logistics, supermarket, tobacco, hydropower, mobile government affairs, mobile Police, posts and other industries

Settings

| Point | Parameter | |
|--------------------------|-------------------------|--|
| Print setting | Printing Method | Thermal Online |
| | Effective print width | 72 |
| | Resolution | 576 Points/Line [8dots/mm] [203] |
| | Printing Speed | 90 mm/s |
| | Interface | USB (Standard USB 2.0 communication protocol, (Windows support, Linux, Android, iOS) Bluetooth (Bluetooth 2.0, Bluetooth 3.0 + 4.0, support Android, iOS) WiFi (2.4 GHz, ATA, AP, ATA + AP Mode) |
| | Online Spacing | 3.75 mm [Can Adjust line spacing by order] |
| | Line No. | Font A: 48 character/ Character/Line of characters b: 64 Single, Traditional Chinese-24 lines |
| | Character | The standard GB18030 simplified/Traditional Chinese Character Library |
| Bar code character | Character Size | Character of SCN [Police has] [1.5 × 3.0 mm] [12 × 24 points] Police b [1.1 × 2.1 mm] [9 × 17 points] Simplified/Traditional [3.0 × 3.0 mm (24 × 24dots)] |
| | Extended Character Set | pc437/Katakana/PC850/PC860/pc863/PC865/Westeurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/East/PC858/IranII/Latvian/Arabic/PT151, 1251/PC737/WPC/1257/Thai/Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151, 1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai) |
| Graphic printing | Bar Code | 1 D Barcode [UPC-A/UPC-E/Jan13 (EAN13)/JAN8 (EAN8) Code39/ITF/ Codabar/code93/code128 2d. Bar code [QR Code] |
| | Graphics Printing | Supports download and bitmap printing |
| Energy Saving Mode | Smart Energy saving | Support |
| | Variable Speed printing | Support |
| | Consumption | Support |
| | Dormancy | Support |
| Dection | Sensor | Lack of paper detection |
| Indicator | Power Display | Support |
| | Load Indicator | Support |
| | Lack of paper | Support |
| | Beep | Lack of paper, abnormal alarm printing |
| Paper | Type | Thermal |
| | Width | 79.5 mm |
| | Thickness | ≤ 0.12 mm |
| | Diameter | ≤ 40 mm |
| | Feed | Easy [Clamshell Feed] |
| Print commands | Commands | ESC/POS |
| Power | Type | Rechargeable Lithium Polymer Battery |
| | Capacity | 2500mah/7.4v, can be charged more than 800 times Durable printing 150 meters or 4 hours under normal use |
| | Charger | 9.0 V/2 A |
| Buffer | Entry | 4 |
| | Nv Flash | kb |
| Physical characteristics | Weight | G |
| | Dimension | 114 * 103 * 50 (mm) |

| | | |
|-------------|----------------------------|--|
| Environment | OF | Temp[5 ~ 45] Moisture[10 ~ 80% |
| | Storage | Temp[-10 ~ 50] Moisture[10 ~ 90%] No Dew |
| Reliability | Print The life of the head | 50 Printing Density ≤ 12.5 |
| Software | Pilot | Android, iOS, Linux, WinXP, Win7, Win8, Win 8.1, Win10 |