# 80mm receipt printer for POS bill with auto cutter (OCPP-88A)

## **Keywords:**

### receipt printer, Bill receipt printer, printer for POS

### **Features:**

- 1. Unique appearance with reliable mold;
- 2. High-speed printing at speeds up to 300 mm / sec;
- 3. Optional automatic cutter;
- 4. Line and options Cordless Telecommunications
- 5. Provide a variety of interfaces: USB, USB + serial, USB + LAN, USB + serial + LAN; and WiFi + USB + Bluetooth + USB LAN
- 6. audible alarm application support is available for the kitchen;
- 7. Support various kinds of one-dimensional and two-dimensional bar code printing;
- 8. Supports a variety of international languages;
- 9. Provides SDK for Android;
- 10. Reliable print head life and one hundred kilometers;
- 11. EP SON Compatible ESC / POS command.

### **Parameters:**

Printing Methods	Thermal line printing		
Printed characters	576dots / line (default), 512dots / line;		
	Characters: Simplified Chinese points of 24x24, 18030 are medium, medium for Taiwan and Hong		
	Kong, traditional (complex Font), ANK character;		
Font	A: 12 * 24dots, 1.5 (W) * 3.0 (H) mm;		
	B: 9 * 17dots, 1.1 (width) * 2.1 (H) mm		
	Simplified / Traditional: 24 * 24dots, 3.0 (W) * 3.0 (H) mm		
Barcode Types	JUPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODABAR / ITF / CODE39 / CODE93 / CODE128, QR		
	code		
Print speed	250 mm / sec as a single interface to 300mm / sec dual interface and triple interface		
Interface	USB, USB + serial, USB + LAN, USB + Serial + LAN + Wireless USB, Bluetooth + USB + LAN		
Print command	Compatible with EPSON ESC / POS command		
Driver	In Win9X / Window XP / VISTA Win / WIN2000 / Win2003's / Win / Win 7 8 / win8.1 / Linux is, and		
	ESPON, SDK Provides compatibility with Android.		
Print width	79.5 ± 0.5 mm (printing width 72)		
Paper diameter	83 mm		
Paper Thickness	0.06-0.08mm		
Knife	Automatic cutter (optional)		
Reliability Print	One hundred kilometers		
Power	DC24V / 2.5A		
Temperature	0-45 degrees Celsius		

In contrast humidity	10-80%		
Dimensions	190 * 145 * 145 (MM)		
Weight	1.60 kg		
Ordering Information	P / N	Description	
	OCPP-U-88A	USB ports supporting automatic cutter	
	OCPP-88A-UR	USB + serial ports, Supporting automatic cutter	
	OCPP-UL-88A	USB + LAN ports supporting auto-cutter	
	OCPP-88A-URL	USB + serial + LAN ports with automatic cutter	
	OCPP-88A-W	+ Wireless USB, automatic cutter	
	OCPP-88A-BUL	Bluetooth + USB + LAN, supporting automatic cutter	
	OCPP-88A-U0	USB port, no automatic cutter	
	OCPP-88A-UR0	USB + serial, no automatic cutter	
	OCPP-88A-UL0	USB + LAN port, no automatic cutter	
	OCPP-88A-URL0	USB + serial + Lan port, without automatic cutter	
	OCPP-88A-W0	+ Wireless USB, no automatic cutter	
	OCPP-88A-BUL0	LAN + Bluetooth + USB, no automatic cutter	

x x x x x x