

All in One Touch Screen POS machine with POS thermal printer  
(M / N: POS -E15)

Parameter:

Template	POS -E15.6-W / POS -E15.6-A
Main Council	Intel Celeron Processor J1900 quad core 1.99solHz (Windows)
Main Council	RK3288 Quad core Processor (Android)
OS-1	Windows7 (Beta)
OS-2	android 6.0
Memory-1	2 GB SSD RAM 32 GB (Windows)
Memory-2	2 GB of RAM 8 GB EMMC (Android)
Touch screen	Multipoint capacitive touch
Screen size	15.6 inches, 16: 9
Resolution	1366 * 768
Customer display	LCD customer display (default), Options: 11.6 or 15.6 inch non-touch screen, VFD customer display,
Color	Black
Printer	Large 58mm thermal gear printer or 80mm thermal printer with automatic cutter (Options)
I / O port(J1900)	USB *6
	RJ45 * 1
	RJ11 * 1(optional)
	VGA * 1
	HDMI * 1(for the vice screen)
	DB9 RS232 door * 2 (can contain up to 4 COM ports)
I / O Port (RK3288)	RJ11 * 1 (Opional)
	TF slot * 1
	RJ45 * 1
	HDMI * 1 (for vice screen)
	USB * 2 (can add 4 ports for optional)
	DB9 RS232 port * 1
Operating temperature	0 °C to 40 °C
Other features (Android)	Bluetooth, WIFI
ORoptional items(Windows)	RFID,MSR, I-Button VFD LCD, DB25 parallel port, DB9 RS232 port * 4
ORoptional items(Android)	3G, 4G, VFD LCD display, RFID,MSR, I-Button
Storage temperature	-20 °C to 60 °C
Power adapter	Power supply AC 110-240 V / 50-60 Hz Entrance, 12 / 24V output ddepending on the printer



POS-E15





POS-E15





POS-E15

