### Auto Sense Laser USB Handheld Barcode Scanner (Model:OCBS-LA06)

Performance Characteristics         Light Source:       Visible laser (650-670nm)         Scan Rate:       100 scans per second         Reading Distance       2.5 ~600mm (100% UPC/EAN)         Scanner Type:       Bi-directional         Resolution:       0.10mm (4mil) at PCS 0.9         Print Contrast Minimum:       20%, minimum reflective difference (@650nm)         Decode Capability:       UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39         39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, code interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, variants, Chinese 2 of 5         Physical Characteristics       PS2, RS232, USB         Interfaces Supported:       PS2, RS232, USB         Voltage:       DC+5V+/-5%         Current:       100 mA         Idle Current:       <40 mA	
Scan Rate:       100 scans per second         Reading Distance       2.5 ~600mm (100% UPC/EAN)         Scanner Type:       Bi-directional         Resolution:       0.10mm (4mil) at PCS 0.9         Print Contrast Minimum:       20%, minimum reflective difference (@650nm)         Decode Capability:       UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39         39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, cod       interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, variants, Chinese 2 of 5         Physical Characteristics       Interfaces Supported:       PS2, RS232, USB         Voltage:       DC+5V+/-5%         Current:       100 mA	
Reading Distance       2.5 ~600mm (100% UPC/EAN)         Scanner Type:       Bi-directional         Resolution:       0.10mm (4mil) at PCS 0.9         Print Contrast Minimum:       20%, minimum reflective difference (@650nm)         Decode Capability:       UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39         39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, co       interleaved 2 of 5,discrete 2 of 5, code 93, MSI, code 11, ATA, variants, Chinese 2 of 5         Physical Characteristics       Interfaces Supported:       PS2, RS232, USB         Voltage:       DC+5V+/-5%         Current:       100 mA	
Scanner Type:       Bi-directional         Resolution:       0.10mm (4mil) at PCS 0.9         Print Contrast Minimum:       20%, minimum reflective difference (@650nm)         Decode Capability:       UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39         39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codinterleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, variants, Chinese 2 of 5         Physical Characteristics         Interfaces Supported:       PS2, RS232, USB         Voltage:       DC+5V+/-5%         Current:       100 mA	
Resolution:       0.10mm (4mil) at PCS 0.9         Print Contrast Minimum:       20%, minimum reflective difference (@650nm)         Decode Capability:       UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39         39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, co         interleaved 2 of 5,discrete 2 of 5, code 93, MSI, code 11, ATA, variants, Chinese 2 of 5         Physical Characteristics         Interfaces Supported:       PS2, RS232, USB         Voltage:       DC+5V+/-5%         Current:       100 mA	
Print Contrast Minimum:       20%, minimum reflective difference (@650nm)         Decode Capability:       UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39         39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codinterleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, variants, Chinese 2 of 5         Physical Characteristics         Interfaces Supported:       PS2, RS232, USB         Voltage:       DC+5V+/-5%         Current:       100 mA	
Decode Capability:       UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39         39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, cod         interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, variants, Chinese 2 of 5         Physical Characteristics         Interfaces Supported:       PS2, RS232, USB         Voltage:       DC+5V+/-5%         Current:       100 mA	
39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, co         interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, variants, Chinese 2 of 5         Physical Characteristics         Interfaces Supported:       PS2, RS232, USB         Voltage:       DC+5V+/-5%         Current:       100 mA	
Interfaces Supported: PS2, RS232, USB Voltage: DC+5V+/-5% Current: 100 mA	odabar,
Voltage: DC+5V+/-5% Current: 100 mA	
Current: 100 mA	
Idle Current: < <40 mA	
Power Source: Host power or external (RS232) power supply	
Scanning Angle Inclination 45° Elevation 60°	
Dimensions: L165.42mm X W69.72mm X H89.67mm	
Weight: 140g (without stand)	
Stand With	
Color: Ivory and black	
User Environment	
Operating Temperature: 0degree C~50degree C	
Storage Temperature: -40degree C~ 70degree C	
Humidity: 5~95% relative humidity, non-condensing	
Electrostatic Discharge: Confirm to +/-15KV air discharge and +/-8KV of contact discharge	irge
Drop Specifications: Withstands multiple 1.5m drops to concrete	
Safe:	
EMI/RFI: FCC Class A and CE	
Laser Safety: CDRH class 2 laser product	

### **Product Details:**













# All-round show





## Parameter

Light Source:	Visible laser (650-670nm)
Scan Rate:	100 scans per second
Reading Distance	2.5~600mm (100% UPC/EAN)
Scanner Type:	Bi-directional
Resolution:	0.10mm (4mil) at PCS 0.90
Print Contrast Minimum:	20%, minimum reflective difference (@650nm)
Decode Capability:	UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5

Interfaces Supported:	PS2, RS232, USB	
Voltage:	DC+5V+/-5%	
Current:	100 mA	
Idle Current:	<40 mA	N
Power Source:	Host power or external (RS232) power supply	
Scanning Angle	Inclination 45° Elevation 60°	
Dimensions:	L165.42mm X W69.72mm X H89.67mm	
Weight:	140g (without stand)	
Stand	With	
Color:	Ivory and black	
User Environment		
Operating Temperature:	0°C~50°C	
Storage Temperature:	~40°C~ 70°C	
Humidity:	5~95% relative humidity, non-condensing	
Electrostatic Discharge:	Confirm to +/-15KV air discharge and +/-8KV of contact discharge	
Drop Specifications:	Withstands multiple 1.5m drops to concrete	23
Safe:	www.	
EMI/RFI:	FCC Class A and CE	
Laser Safety:	CDRH class 2 laser product	

## Shipping and payment

- 1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
- 2. EXPRESS: around 3-7 working days to arrive
- 3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which arriv www.ocomin
- destination port
- 4. By sea: depend on which destination port
- T/T. 04 5.
- 6. Western Union
- 7. Escrow
- 8. L/C

### Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.











#### 1. MOQ policy

No MOQ limitation for the standard products, but the unit price is different, bigger quantity better price.

For customized production, you can discuss the MOQ with our sales representative directly.

#### 2. Sample Availability & Policy

After customers confirmed the specification, we are very glad to provide samples for testing and qualification.

All samples should be paid before shippment, the samples price is a higher than mass order. When the mass order placed, we can return you the samples cost, or send you more piece products with the shippments.

You can buy the samples from us directly using t/t, western union, or paypal. And you can also buy it on our online store.

#### 3. Warranty

OCOM is dedicated to providing most cost-effective products and services with reliable quality that will meet customers'satisfication;

We was qualified by global fortune 500 company, and we have the top 1 level trade assurance which 100% protect your money and lead time.

Our warranty of the products is about 12+1 months from the shipment normally, some designated models can have as long as 24 months warranty;

Any product within 30 days of delivery failure occurs shall be deemed invalid delivery (DOA). DOA products will give priority to the replacement, and shipped by courier.

For mass order, we would like to supply some spare parts with shipment for local quickly repair. And after that, you can returned failure parts for rework and analysis.

#### 4. Payment Terms

For mass order, you can pay us by using T/T, LC, Western Union, Escrow or others. About samples order, T/T, Western Union, Escrow,Paypal are acceptable.Currently,you can pay using Moneybookers, Visa, MasterCard and bank transfer. You can also pay with select debit cards including Maestro, Solo, Carte Bleue, PostePay, CartaSi, 4B and Euro6000.

#### 5. Shipment

We accept all kinds of shipping ways including: express, air, sea, truck, or pick up by customers personally.

#### 6. Customer

Our main customers from Eruopean, Australia, and the fast growing South America, Africa, Russia...,

We have servered more than 2300 customers from 159 countries, including the global fortune 500 company like Unilever, O2.....50 of them are the biggest distributor in the local teritories.

#### Why You Choose OCOM?

·Leading One-Stop POS and Auto-ID Related Products Supplier Qualified by Global Fortune 500 Companies ·Tier 1 customers including Unilever, O2, Star...

·2300+ Customers Cover 159 Countries;

·11 Years OEM/ODM Experience.

·Top 1 Level Trade Assurance in POS industrial quarantee quality and shipment date

·Fast respondes and professional service
·ISO, FCC, CE, Soncap, POA, BIS, and other Certificates
·12+1 months wanrranty.
·Shortlisted in "China Best Employer Award"
·Belief: Integrity Based, Strive for Excellence, Win-win Cooperation