# Auto Sense Portable Laser Barcode Scanner With Stand (OCBS-LA09)

#### **Specification:**

Specification.	
Performance Characteristics	
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	Auto Sense
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	30%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese code, GS1 DataBar (RSS)series
Scanning Angle	$\pm65^{\circ}$ (tilt); $\pm60^{\circ}$ (pitch); $\pm42^{\circ}$ (yaw)
Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB for option
Voltage:	5V DC±5%
Current:	85 mA (Operating); 100 (Max)
Indicator	Beeper, LED
Material	ABS+PC
Stand	With
Dimensions:	156*68*83 mm (L*W*H)
Weight:	235g
Color:	Grey or black
User Environment	
Operating Temperature:	0°C~45°C
Storage Temperature:	-40°C~60°C
Humidity:	5%-90% (non-condensing)
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge
Ambient Illumination	0 ~ 100,000 LUX
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface
Laser classification	EN60825-1, Class 1

#### **Product Details:**



## Product Picture















## All-round show





### Parameter

Performance Characteri	stics
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU ATTO	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	Auto Sense
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	30%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Triontic Code 39, Code 128, Code 128 Full ASCII, Codebar

inc.c	Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code, GS1 DataBar (RSS) series	
Scanning Angle	±65°(tilt); ±60°(pitch); ±42°(yaw)	240
Physical Characteristic	s www.occ	
Interfaces Supported:	PS2, RS232, USB	1
Voltage:	5V DC±5%	1
Current:	85 mA (Operating); 100 (Max)	1
Indicator	Beeper, LED	1
Material	ABS+PC	1
Stand	Optional	1
Dimensions:	156*68*83 mm (L*W*H)	ĺ
Weight:	235g	
Color:	Grey and black	244
User Environment	WW.	1
Operating Temperature:	0°C~45°C	1
Storage Temperature:	-40°C~60°C	
Humidity:	5%-90% (non-condensing)	1
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge	
Ambient Illumination	0 ~ 100,000 LUX	1
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface	
Laser classification	EN60825-1, class 1	

## Shipping and payment

- 1. 1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
- 2. EXPRESS: around 3-7 working days to arrive
- 2 INITERNATIONIAL AIR MAIL usually around 2-4 days to arrive will also depend on which

J. W.W.W.

- destination port
- 4. By sea: depend on which destination port
- 5. T/T
- 6. Western Union
- 7. Escrow
- 8. L/C

#### **Company Profile**



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com,

Together we quest for the best.











