

# Auto cutter 80mm pos printer receipt printer thermal

## Specification

|                      |  |
|----------------------|--|
| Printing method:     | Direct thermal   |
| Printing speed:      | 230mm/s□260mm/s  |
| Roll width:          | 79.5±0.5mm   |
| Print diameter:      | Φ80mm  |
| Paper thickness:     | 0.06-0.08mm  |
| Column capacity:     | 576dots/line□512 Dots/line   |
| Line's pacing :      | 3.75mm□Adjustable by commands□   |
| Print command:       | Compatible with the ESC/POS command  |
| Interface type:      | Serial+USB+Lan/36P parallel port/25P serial +USB/LAN   |
| Cutters life:        | 1million cuts  |
| Print head life:     | 100 km   |
| Input buffer :       | 2048Kbytes   |
| NV Flash:            | 256Kbytes  |
| Power adaptor:       | AC110V/240V□50~60Hz  |
| Power supply:        | DC 24V/2.5A  |
| Cash drawer supply:  | DC 24V/1A  |
| Work environment:    | Temperature(0□45) humidity(10□80%)□Non- condense□  |
| Work environment:    | Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense  |
| Storage environment: | Temperature(-10□60°C); Humidity(10□90%)  |
| Character size:      | ANK□FontA:1.5*3.0mm/ FontB□1.1*2.1mm   |
| Barcode:             | UPC-A/UPC-E/JA□EAN13□/JAN8□EAN8/CODE39/ITF /CODE93/CODE128 QRCode  |
| Characters:          | PC347□Standard Europe□Katakana□PC850□Multilingual□PC860□Portuguese□PC863□Canadian-French□PC865□Nordic□West Europe□Greek□Hebrew□East Europe□Iran□WPC1252□PC866□Cyrillic#2□PC852 □Latin2□PC858□IranII□Latvian□Arabic□PT151□1251□ |



## Relevant documents:

[\\*Specification](#)

[\\*IP Address Configure Manual](#)

[\\*Instruction Manual](#)

[\\*Driver for all windows system](#)

[\\*Driver for Linux](#)

[\\*Printer Parameters Setting Tools](#)

[\\*CD Files](#)