

## 80MM thermal printer with auto cutter

(Model: OCPP -80Y)



### Feature:

Desktop or wall-mounted options.

Support multiple barcode printing

USB, USB + LAN, USB + RS232, optional URL

Support 256KB NV logo storage and 2M large buffer memory.

Small package, save transportation cost

### Technical parameter:

Printing method:	Direct heating
Printing speed:	160 mm/sec
Roll width:	79.5±0.5mm
Printing diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576 dots/line512 dots/line
Line spacing :	3.75mm (adjustable by command)
Print command:	Compatible with ESC / POS commands
Interface Type:	USB, USB + LAN, USB + RS232, USB + RS232 + LAN
Tool life:	Cut 1 million
Print head life:	100 km
Input buffer:	2048Kbytes
NV Flash:	256K bytes
Power Adapter:	AC110V / 240V, 50~60HZ
power supply:	DC 24V / 2.5A

Cash drawer supply:	DC 24V / 1A
working environment:	Temperature (0~45) Humidity (10~80%) (non-condensing)
working environment:	Temperature (0-45) degrees Celsius, humidity (10-80%) non-condensing
Storage environment:	Temperature (-10~60°C); Humidity (10~90%)
Character size:	ANK, FontA: 1.5 * 3.0mm / FontB: 1.1 * 2.1mm
Barcode:	UPC-A / UPC-E / JA (EAN13) / JAN8 (EAN8 / CODE39 / ITF / CODE93 / CODE128, (QR code and PDF 417 optional)
Features:	PC347 (Standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canada-France), PC865 (Northern Europe), Western Europe, Greece, Hebrew, Eastern Europe, Iran, WPC1252, PC866 (Siri Irvine #2), PC852 (Latin 2), PC858, IranII, Latvian, Arabic, PT151 (1251)
Physical characteristics:	Weight: 1.25Kg















Optional power adapter:



Application areas:



## ► Application scenario

Logistics



Warehouse management



Supermarket



Clothing label



Jewelry label



Restaurant



### Related Products:

[Unique 80mm high speed POS thermal printer](#)