

**Auto sense 1D laser barcode scanner suppliers
(Model: OCBS-LA11)**

TECHNICAL PARAMETERS:

| | |
|--------------------------|--|
| Features | |
| light source: | Visible laser (650-670nm) |
| Scanning speed: | 100 scans per second |
| Reading distance | 2.5~600 mm (100% UPC / EAN) |
| Scanner Type: | Two-way |
| Resolution: | 0.10 mm (4MIL) in PCS 0.9 |
| Print Contrast Minimum: | 30% minimum reflectance difference (@ 650 nm) |
| Error rate: | 1/3000000 |
| Decoding capability: | UPC / EAN codes, UPC / EAN with supplements, UCC / EAN128 yards, 39 yards, 39 yards full ASCII code, 39 yards trioptic, 128 yards, 128 yards full ASCII code, Codabar, Interleaved 2 of 5, 25 consecutive Code 93, MSI, Code 11, ATA, RSS variants, Chinese 25 ... |
| Physical Characteristics | |
| Support Interface: | PS2, RS232, USB |
| Voltage: | DC + 5V ± 5% |
| current: | One hundred mA |
| Standby current: | & Lt; 40 mA |
| Power source: | Host power or external (RS232) power supply |
| Scan angle | 45 ° elevation angle 60 ° |
| size: | L165mm X W63mm X H87mm |
| weight: | 129 g (without base) |
| station | Optional |
| Colour: | Grey and black |
| User Environment | |
| Operating temperature: | 0 °C ~40 °C |
| Storage temperature: | -40 °C ~60 °C |
| humidity: | 5~95% relative humidity, non-condensing |
| Electrostatic discharge: | Recognized as +/- 15kV contact discharge air discharge and +/- 8KV |
| Drop specifications: | Can withstand multiple 1.5 m drops to concrete |
| Safety: | |
| EMI / RFI: | FCC A class and CE |
| Laser Safety: | CDRH Class 2 laser products |

Product Details:



Related documents:

You want to know more products INFORMATION?please click here.

[specification](#)

[User's manual](#)