

Barcode Printer with Thermal Printing and Thermal Transfer Printing  
(Model No. : OCBP-003)

Features:

- | Two printing methods available: Thermal Transfer with ribbon and Direct Thermal;
- | Label paper auto position;
- | Labels peel off, tear off automatically;
- | Compatible with plenty of label software;
- | BMP, PCX images download store;
- | Parallel, USB, Serial and Power port available;
- | Support PDF417, QR CODE, DOTMATRIX;
- | Suit for thermal paper rolls or self-adhesive labels;

Specifications:

|                      |   |
|----------------------|---|
| Printer Model        | OCBP-003  |
| Resolution           | 300 DPI (8 dot / mm)  |
| Printing Method      | Direct Thermal / Thermal Transfer   |
| CPU                  | 32 BIT  |
| Sensor               | Type: Label gap<br>Detection: label length auto sensing or program command setting  |
| Printing Speed       | 2 ~ 5inch / Sec   |
| Max Printing Length  | 1651 mm   |
| Max Printing Width   | 81mm (3.18 ")   |
| Media                | Paper Roll External Diameter: Maximum Diameter 127mm<br>Paper Roll Axis: 26 mm<br>Paper Width: 20mm (0.78 ") ~ 90mm (3.54")<br>Paper Thickness: 0.06mm (2.36 mil) ~ 0.254mm (10 mil)<br>Media Type: Label gap, Continuous, folded |
| Ribbon               | Types: Outward Roll<br>External Diameter: 67mm (Max)<br>Length 300M<br>Width: 30 mm ~ 90 mm<br>Core Inner Diameter: 25.4mm (1inch)<br>Material: outward rolling   |
| Interface            | Parallel Port + USB + Serial  |
| Transmission Setting | Baud Rate 9600, XON / XOFF, RTS / CTS   |
| Control panel        | LED * 2: Ready, Status<br>Function Key * 1: Feed  |
| Power                | AC 18V, 4000mA  |
| Environment          | Operating Temperature: 5 ~ 45 Degree C Humidity 25-85%<br>Storage Temperature:: -10 ~ 50 Degree C Humidity 10 ~ 90%   |
| Physical Dimension   | Size: 186 (W) × 180 (H) × 290 (D)<br>Weight: 2.4KG (net)  |