

Bluetooth Mini Wireless Barcode Scanner With Screen

Specification

Physical Parameter	
Size	152mm(L)×77mm(H)×29mm(W)
Weight	≈500g
Display Screen	Color 4.0 inch QVGA imitative glass durable touch screen TFT-LCD, 650000 colors, 480*800 (QVGA size) The brightness of LED Backlight is adjustable
Expand Port	SIM card, PSAM card, Micro SD (TF) Card
Communication Interface	USB2.0 Device, RS-232□Optional□
Input Mode	Standard Stylus, Handwriting, touching input or keyboard input
Battery Capacity	Rechargeable Li-polymer Battery 3.7V 4000mAh Optional
Frequency	8Ω1W speaker
Key	29pcs soft silicon key
Performance Parameter	
CPU	Dual-Core ARM Cortex-A9 Dual-core 1.5G
RAM	1G RAM
Flash ROM	Standard 4G NAND Flash Storage Micro SD/TF port (Max up to 32G)
Data Communication	
WI-FI	Support IEEE802.11b/g protocol, it need effective wireless LAN signal cover
WCDMA	UMTS2100/900MHz UMTS1900/850MHz GSM850/900/1800/1900MHz
CDMA2000	CDMA2000 1x,CDMA2000 EV-DO Rev 0,CDMA2000 EV-DO Rev A Supports BC0(800MHz band),BC1(1900MHz band)
Bluetooth	Support Bluetooth 2.0+EDR, transmission distance is 5-10m
Operating Environment	
Operating Temperature	−20°C to 50°C
Storage Temperature	−25°C to 70°C
Environment Humidity	5%RH--95%RH(no condensation)
Drop Specifications	6 sides can bear impact from 1.5m drop to cement floor in the range of operating temperature
Roll Specifications	1000 times/0.5m, roll on 6 sides contact area
Sealed Environment	IP67