## **Mini Magnetic Stripe Card Reader**

(Model No.: CR1300)

## Features:

- 1. Compatible with Android System.
- 2. All 3 tracks can set to 75/210 BPI;
- 3. USB or Serial interface.
- 4. Long service life (500,000 card passes).
- 5. Suitable for all ISO7811/7812, ANSI, AAMVA and CA DMV magnetic cards.



**Specifications:** 

Dimension Weight Power Supply Power consumption Operation Locus Card Standard	90mm(L) x 26mm(W) 85g(approx.) +5V DV ±5% 40mA (max.) Indoor use ISO7811/7812	) x 28mm(H)	
Track Position	ISO 1 (IATA)	ISO 2 (ABA)	ISO 3 (MINTS)
Recording Density	210 BPI	75 BPI	210 BPI
Recording Capacity	79 Characters (7bits)	40 Characters (5bits)	107 Characters (5bits)
Interface Card Thickness Head Function Operation Speed Life of Head Error Rate Temperature	USB / Serial Plastic 0.76 ± 0.08mm Read only 1.5mm 10 ~ 150cm/sec 500,000 card passes (1 pass : one swipe) Less than 0.5% (JSE Test card) Storage : -30°C to +70°C Operating : -20°C to +70°C		
Humidity	Storage . 0% to 95%	RH Operating : 20% to 90%	