Cheap 80mm POS Bluetooth Thermal Receipt Printer with Auto-cutter

(Model No.: OCPP-80X)

Features:

Supports multi 1D bar codes and 2D bar codes printing.

100M Ethernet port, ultra high speed data transmission.

Supports 256KB NV Logo storage and 2M big buffer memory.

Supports black mark detection and order reminding function,

USB+RS232+LAN three types of communication Ports

250mm/s high speed printing

Technical parameters：

Printing method:	Direct thermal
Printing speed:	250mm/s
Roll width:	79.5±0.5mm
Print diameter:	Φ80mm
Paper thickness:	0.06-0.08mm
Column capacity:	576dots/line512 Dots/line
Line’s pacing :	3.75mm（Adjustable by commands）
Print command:	Compatible with the ESC/POS command
Interface type:	Serial+USB+Lan
Cutters life:	1million cuts
Print head life:	100 km
Input buffer :	2048Kbytes
NV Flash:	256Kbytes
Power adaptor:	AC110V/240V，50~60Hz
Power supply:	DC 24V/2.5A
Cash drawer supply:	DC 24V/1A
Work environment:	Temperature(0～45) humidity(10～80%)（Non- condense）
Work environment:	Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense
Storage environment:	Temperature(-10～60°C); Humidity(10～90%)
Character size:	ANK：FontA:1.5*3.0mm/ FontB：1.1*2.1mm
Barcode:	UPC-A/UPC-E/JA（EAN13）/JAN8（EAN8/CODE39/ITF /CODE93/CODE128/QRCode/PDF417 (options)
Characters:	PC347（Standard Europe）、Katakana（PC850（Multilingual）、PC860（Portuguese）、PC863（Canadian-French）、PC865（Nordic）、West Europe（Greek（Hebrew（East Europe（Iran（WPC1252（PC866（Cyrillic#2）、PC852（Latin2）、 PC858（IranII（Latvian（Arabic（PT151（1251）
Physical characteristics：	Weight: 1.45Kg; Appearance size: 190×145×143mm (length * width * height)

Aocom®
At your side
OCPP-80X
POWER
ERROR
PAPER
FEED
ISO
FC
CE
RoHS

Aocom®
At your side
OCPP-80X
POWER
ERROR
PAPER
FEED
ISO
FC
CE
RoHS

ocom®
At your side
OCPP-80X
ISO
FC
CE
RoHS

Aocom®
At your side
OCPP-80X
ISO
FC
CE
RoHS

Aocom®
At your side
OCPP-80X
ISO
FC
CE
RoHS

Ocom®
At your side

OCPP-80X

Ocom®
At your side

OCPP-80X

ISO FC CE RoHS

ocom®
At your side
OCPP-80X
ISO
FC
CE
RoHS