

80mm embedded thermal printer

(M/N:OCKP-8004)



- l. 120mm/s printing speed,
- m. 80mm diameter paper house
- n. Support Auto cutter
- o. Support multiple countries language code pages
- p. Support graphical printing
- q. Support NV logo storage and printing

- r. Support multiple 1D and 2D barcode printing
- s. Printer head life 100km,cutter life one million times

| | |
|--------------------------------------|---|
| Model | OCKP-8004 |
| Printing method | Thermal line dot method |
| Paper type | Thermal paper roll |
| Interface | USB +RS232 |
| Resolution | 203dpi(8dots/mm) |
| Paper width | 79.5±0.5mm |
| Printing speed | 120mm/s |
| Effective printing area | 72mm |
| Character set | ASCII□GBK□BIG5 and so on |
| Character set | ANK□(9*17,12*24)□Chinese□□24*24□ |
| Paper roll diameter / inner diameter | Max:80mm; min:13mm |
| Paper thickness | 0.055-0.09mm |
| Print Life | ≥100Km |
| Cutter life | ≥1,000,000cuts |
| Bar-code types | 1D:UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93 2D:QR Code |
| No Paper detection | Photoelectric detection |
| Paper near end detection | Photoelectric detection |
| Power adaptor | DC24V/2A |
| Cash drawer output | DC 24V/1A □optional) |
| Dimensions | 114.8*132*86.4mm |
| weight | 360g |
| Package box | 145*125*95mm/410g |
| Operating temperature | 0°C~50°C |
| Operating humidity | 20%RH ~85% RH |
| Storage temperature | -20°C~60°C |
| Storage humidity | 5% ~90%RH |









