Cheap USB 58mm mini pos thermal receipt printer (OCPP -58E)

ProductIntroduction:

OCPP -58E is a well-designed economic printer for common thermal bill printing ,this mold is with solid material, Exquisiteworkmanship. Transparent cover design, simple and fashion, easy for users toknow the paper rolls' Using status, OCPP -58E adopt built-in Power supply, notonly can save space, but also easy for users to configure and use the printers. It's a very good choice for economical printing.

ProductFeatures:

- •Simple and fashion, With solid material, exquisitework manship.
- ●Easy paper install structure, simple and convenient tooperate
- •Built-in power supply design, to save space and moreconvenient to configure;
- ●Transparent cover design, the user can know the paperroll's using status anytime;
- ●Support GB18030 big font, easy to print Uncommoncharacters
- Support multi language print, suitable for users all overthe world;
- Support download and print LOGO&graphics;
- Support Windows, Linux, Android and IOS system printing

ApplicationArea:

Shoppingmalls, restaurants, stores, warehousing, taxation, banking, medical, pos tal

Parameters:

| Items | | Parameters |
|-----------------------------|-----------------------------------|--|
| | Printing Method Printing Width | Thermal Line 48MM |
| | Resolution | 384dots/Line(8dots/mm,203dpi) |
| | Printing Speed | 90mm/Second |
| Print | Interface Type Line Spacing | USB,USB+Bluetooth 3.75 mm(Can adjust line spacing by command) |
| parameters | Line No. | Font A:32 character (Line |
| | | Font B: 42 character/Line |
| | | Simple,traditional Chinese-16 lines |
| | Character | Standard GB18030 simplified / traditional Chinese Fonts |
| | Character Size | ANKcharacter, Font A:1.5 x3.0 mm(12 x 24dots) |
| Bar code | Extended | Font B:1.1×2.1mm(9×17dots) Simplified/Traditional Chinese:3.0×3.0mm (24×24 dots) PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/ |
| character | character set | PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai) |
| | Bar code | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ |
| Comphise | Complian animhina | CODABAR/CODE93/CODE128 |
| Graphics printing | Graphics printing | Supports bitmap download and print |
| Paper | Type | Thermal Roll |
| | Width | 57.5±0.5mm |
| | Diameter Feed Method | ≤60mm Easy feed (Clameshell feed) |
| Print | Commands | casy reed (Clarifestien reed) ESC/ POS |
| commands | | |
| Power | Power Adaptor | Input:AC 100V-240V, 50-60Hz |
| | Casher Drawer | Output:DC 12V/ZA DC 12V/ZA |
| | output | DC 129/1A |
| Buffer | Input Buffer | 4K |
| | NV Flash | 408 |
| Physical characteristics | Weight Dimension | 590g 185*130*112(MM) |
| Environment | Working | 160-112(min) Temp: 5 - 45 ° C, Humidity:10 ~ 80% |
| | Storage | Temp:-10 ~ 50 °C , Humidity::10 ~ 90%(No dew) |
| Reliability | Print Head Life | 50KM(Print density≤12.5) |
| parameter | | |

Relevant documents:

Driver and CD files