

Label printer, barcode label printer, label thermal printer

China Direct Thermal Label Printer with USB + LAN + SERIAL (OCBP-005)

Features:

Label printer, barcode label printer, label thermal printer

- Label paper auto position;
- Labels peel off, tear off automatically;
- Adjust the printer head pressure;
- Compatible with plenty of label software;
- BMP, PCX, BAC images download store;
- Support Serial, USB, LAN together;
- Support PDF417, QR CODE, DOTMATRIX;

Parameter:

Label printer, barcode label printer, label thermal printer

Printer Model	OCBP-005
Resolution	203 dpi (8 dots / mm)
Printing Method	Direct thermal
Head temperature sensor	Varistors thermal
Sensor head position	Microswitch
Detection paper	Photoelectric
Print speed	127 mm / sec (max)? 50.8 mm / sec (min)
Print width	16 mm to 82 mm
Average	Media Type: roll, stickers, labels times, and so on. Average diameter Inside diameter: 25 mm; Diameter: 80 mm
Internal font	Font FONT 0 8? font commonly used one byte
Zoom & amp; amp; amp; amp; amp; Rotating	1-10 times improvement in multiple directions; 0 °, 90 °, 180 °, 270 °, 360 °
Outside the paper type	Rip & amp; amp; amp; amp; amp; peeling
Memory cards	2MB FLASH ROM, 2 MB DRAM
Image	Monochrome PCX, BMP image files can be loaded in Flash, DRAM
Barcode	CODE128, EAN 128, ITF, Code39, Code93, EAN13, EAN13 2, 5, EAN13, EAN8, EAN8 2, 5, EAN8, Codabar, POSTNET, UPC-A, UPCA 2, UPCA 5, UPC-E, UPCE 2, UPCE 5 , CPost, MSI, MSIC, PLESSEY, ITF14, EAN14, PDF417, QR Code, DATMATRIX
Interconnection	USB + RS232 + LAN or USB
Power	Login: 24VDC, 2.5A
Environment	Operating Temperature: 5 ° C to 45 ° C Storage temperature: -40 ° C to 55 ° C Operating Humidity: 20% ~ 80%, non-condensing, free air Storage humidity: & amp; amp; amp; amp; amp; It? = 93% (40 °C), no condensation, free air
Size	Format: D220mm H148mm * W150mm *

Product Details:

Label printer, barcode label printer, label thermal printer

