

# China Factory Handheld 2015 Pos Laser Barcode Scanner

**Features:**

China Factory Handheld 2015 Pos Laser Barcode Scanner  
 Auto-Induction built in, green design;  
 High scan rate and long reading distance;  
 Excellent decode capability;  
 KBW, RS232 and USB supported;  
 Durable construction combined with future-proofing;

**Specifications:**

|                                    |  |
|------------------------------------|--|
| <b>Performance Characteristics</b> |  |
| Light Source:                      | Visible laser (650-670nm)  |
| Scan Rate:                         | 100 scans per second   |
| Reading Distance                   | 2.5 ~600mm (100% UPC/EAN)  |
| Scanner Type:                      | Bi-directional   |
| Resolution:                        | 0.10mm (4mil) at PCS 0.9   |
| Print Contrast Minimum:            | 20%, minimum reflective difference (@650nm)  |
| Decode Capability:                 | UPC/EAN, UPC/EAN with supplementals, UCC/EAN128, code 39, code 39 full ASCII, code 39 trioptic, code 128, code 128 full ASCII, codabar, interleaved 2 of 5, discrete 2 of 5, code 93, MSI, code 11, ATA, RSS variants, Chinese 2 of 5... |
| <b>Physical Characteristics</b>    |  |
| Interfaces Supported:              | PS2, RS232, USB  |
| Voltage:                           | DC+5V+/-5%   |
| Current:                           | 100 mA   |
| Idle Current:                      | <40 mA   |
| Power Source:                      | Host power or external (RS232) power supply  |
| Scanning Angle                     | Inclination 45° Elevation 60°  |
| Dimensions:                        | L165.42mm X W69.72mm X H89.67mm  |
| Weight:                            | 140g (without stand)   |
| Stand                              | With   |
| Color:                             | Ivory and black  |
| <b>User Environment</b>            |  |
| Operating Temperature:             | 0°C~50°C   |
| Storage Temperature:               | -40°C~ 70°C  |
| Humidity:                          | 5~95% relative humidity, non-condensing  |
| Electrostatic Discharge:           | Confirm to +/-15KV air discharge and +/-8KV of contact discharge   |
| Drop Specifications:               | Withstands multiple 1.5m drops to concrete   |
| Safe:                              |  |
| EMI/RFI:                           | FCC Class A and CE   |
| Laser Safety:                      | CDRH class 2 laser product   |

**Products Details:**



**Relevant documents:**

Do you want to know more product information?Please Click here.

[Specification](#)

[User's Manual](#)