

China factory supply roll label printer (Model: OCBP-005)

Specifications:

| | |
|-------------------------|---|
| Printer Model | OCBP-005 |
| Resolution | 203 DPI (8 dots / mm) |
| Printing Method | Direct Thermal |
| Head temperature sensor | Thermal varistor |
| Head position sensor | Micro Switch |
| Paper detection | Photoelectric sensors |
| Print speed | 127 Mm / sec (max); 50.8mm/sec (minutes) |
| Print width | 16 Mm to 82 mm |
| Media | Media Type: roll, stickers, labels fold, and so on. Media Diameter: inner diameter: 25 mm; diameter: 80 mm |
| Internal Font | Typeface 0 FONT 8; commonly used in single-byte fonts |
| Enlarge & Rotary | 1-10 fold amplification in multiple directions; 0 degrees, 90 degrees, 180 degrees, 270 degrees, 360 degrees rotation |
| Off the paper type | Tear & peeling |
| Memory Cards | 2MB FLASH ROM, 2MB of DRAM |
| Image | Monochrome PCX, BMP image files can be loaded into FLASH, DRAM |
| Barcode | CODE128, EAN128, ITF, Code39, Code93, EAN13, EAN13 +2, EAN13 +5, EAN8, EAN8 +2, EAN8 +5, CODABAR, POSTNET, UPC-A, UPCA +2, UPCA +5, UPC-E, UPCE +2, UPCE +5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14, PDF417, QR CODE, DATMATRIX |
| Interface | USB + RS232 + LAN or USB |
| Power | Input: 24VDC, 2.5A |
| Environment | Operating temperature: 5 degrees C to 45 degrees C Storage temperature: -40 degrees C to 55 degrees C Operating Humidity: 20% ~ 80%, non-condensing, free air Storage humidity: <= 93% (40 °C), non-condensing, free air |
| Size | Size: D220mm * H148mm * W150mm |

Product Details:

