

Handheld 1D/2D Barcode Reader (Model: OCBS-2004)

Specifications:

Performance Characteristics		
Image Sensor:	CMOS	
Resolution:	752 * 480	
Light Source:	LED(622 nm - 628 nm)	
Light Intensity:	330 LUX (130 mm)	
Illumination:	0 ~ 100,000 LUX	
Symbology:	2D	PDF417, QR Code(Model 1/2), Data Matrix(ECC200, ECC000, 050, 080,100,140), Aztec, Maxicode, etc.
	1D	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar,etc.
Precision:	≥ 5mil	
Depth of Scan Field:	35 mm ~ 210 mm	
Print Contrast Signal:	≥ 30%	
Roll/ Pitch/ Skew:	360°/±60°/±60°	
Physical Characteristics		
Interface:	RS232 / USB	
Power Consumption:	2 W	
Voltage:	DC 5 V (4.5-5.5V)	
Current:	Idle	78 mA (idle) 400 mA(working) 18 mA (standby)
Weight:	235 g	
Dimensions:	156 * 68 * 83 mm	
User Environment		
Operate Temperature:	-5degree C~+45degree C	
Storage Temperature:	-40degree C~+60degree C	
Humidity:	5% - 95%(non-condensing)	
Safe		
Certificates:	FCC Part15 Class B, CE EMC Class B	

Product Details:



Relevant documents:

Do you want to know more product information?Please Click here.

Specification
User's Manual