

# USB and Wireless Laser Barcode Scanner (Model: OCBS-W600 )

## SPECIFICATION:

PHYSICAL CHARACTERISTICS	
<b>Light Source:</b>	Visible Laser Diode (VLD) @ 650 nm-670nm
<b>Scanner Dimensions:</b>	164mm * 67mm * 95mm(W * H * D)
<b>Receiver Dimensions:</b>	130mm*45mm*129mm(W * H * D)
<b>Material:</b>	ABS+TPR /Aluminium alloy
<b>Weight:</b>	235g
<b>Scanning Mode:</b>	Hand-held; bidirectional Scanning Mode.
<b>Indicator Light:</b>	LED Red and Blue
<b>Buzzer:</b>	Buzzer Volume Adjustable
PERFORMANCE CHARACTERISTICS	
<b>Width of Scan Field:</b>	60mm@30mm□From engine face□ 98mm@100mm□from engine face□
<b>Depth of Scan Field:</b>	2.5-600mm□Contrast 0.9 Density 0.25□
<b>Scan Speed:</b>	100 scans/sec
<b>Scan Precision:</b>	0.10mm□4mil□ PCS0.9
<b>Bit Error Rate:</b>	1/(5million)
<b>Decode Capability:</b>	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN128, Code39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5
<b>Battery:</b>	3.7V/750mAh,Li-ion
<b>Charge Time:</b>	3.0 Hours
<b>Scan Time:</b>	30 Hours
<b>Current:</b>	100mA (working); 40mA(standby)
<b>Angles:</b>	Pitch:60°; Tilt: 45°
<b>Communication Distance:</b>	30m
<b>Working Frequency:</b>	2.4G
<b>Communication Interface:</b>	USB
USER ENVIRONMENT CHARACTERISTICS	
<b>Temperature:</b>	0degree C to 50degree C (Operating), -40degree Cto 70 degree C (Storage)
<b>Relative Humidity:</b>	5%-90%(Non-Condensing)
<b>Drop Specification:</b>	Withstands repeated 1.5m drops to concrete surface
<b>Ambient Illumination:</b>	0~100,000 LUX
<b>Electrostatic Discharge:</b>	Conforms to ±12KV air discharge and ±6KV of contact discharge
<b>Safety Certificate:</b>	CE, FCC, Class 2, RoHS

## Product Details:

