

## Cheap auto cutter 80mm thermal printer

[model] **OCPP-809** [

Parameters:

|                      |   |                                     |
|----------------------|---|-------------------------------------|
| Printing Method      | Thermal line printing   |                                     |
| Printing Character   | 576dots/line (default), 512dots/line;<br>Characters : Simplified Chinese 24x24 point, support 18030 font library, support Taiwan and HK traditional (complex font), ANK characters; |                                     |
| Font                 | A: 12*24dots,1.5(W)*3.0(H)mm;<br>B: 9*17dots,1.1(W)*2.1(H)mm<br>Simplified/Traditional : 24*24dots, 3.0(W)*3.0(H)mm   |                                     |
| Barcode Type         | JUPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128, QR code   |                                     |
| Printing Speed       | 250mm/sec for a single interface ,300mm/sec for Double interface or three interfaces  |                                     |
| Interface            | USB, USB+Serial, USB+ LAN, Wifi+USB, or USB+ Serial+ LAN  |                                     |
| Printing Command     | Compatible with EPSON ESC/POS commands  |                                     |
| Drivers              | Win9X/ Window XP /Win2000/Win2003/Win Vista/ Win 7/ Win 8/win8.1/Linux, compatible with ESPON, SDK for Android available.   |                                     |
| Printing Width       | 79.5±0.5mm( print width 72mm)   |                                     |
| Paper Diameter       | 83mm  |                                     |
| Paper Thickness      | 0.06-0.08mm   |                                     |
| Cutter               | Auto cutter (optional)  |                                     |
| Printing Reliability | 100km   |                                     |
| Power                | DC24V/2.5A  |                                     |
| Temperature          | 0-45 degree C   |                                     |
| Contrast Humidity    | 10-80%  |                                     |
| External Dimension   | 190*145*145(mm)   |                                     |
| Weight               | 1.60kg  |                                     |
| Order information    | P/N   | Description                         |
|                      | OCPP-809-U  | USB, with auto cutter               |
|                      | OCPP-809-UR   | USB+Serial, with auto cutter        |
|                      | OCPP-809-UL   | USB+Lan, with auto cutter           |
|                      | OCPP-809-W  | Wifi+USB, with auto cutter          |
|                      | OCPP-809-URL  | USB+Serial+Lan, with auto cutter    |
|                      | OCPP-809-U  | USB, without auto cutter            |
|                      | OCPP-809-UR   | USB+Serial, without auto cutter     |
|                      | OCPP-809-UL   | USB+Lan, without auto cutter        |
|                      | OCPP-809-W  | Wifi+USB, without auto cutter       |
|                      | OCPP-809-URL  | USB+Serial+Lan, without auto cutter |