

|                                      |                                                                                                                                                                                                                               |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Model</b>                         | OC-PP-80S                                                                                                                                                                                                                     |
| <b>Name</b>                          | 80mm desktop thermal printer with auto cutter                                                                                                                                                                                 |
| <b>Color</b>                         | Black                                                                                                                                                                                                                         |
| <b>Interface</b>                     | USB/USB+LAN/USB+BT/USB+WIFI/URL+WIFI/URL+BT                                                                                                                                                                                   |
| <b>Power supply</b>                  | Input: AC 100V-240V 50-60Hz Output: DC 24V/2.5A                                                                                                                                                                               |
| <b>Cash drawer</b>                   | DC 24V/1A                                                                                                                                                                                                                     |
| <b>Printer head lifespan</b>         | 150km                                                                                                                                                                                                                         |
| <b>Cutter</b>                        | Auto cutter                                                                                                                                                                                                                   |
| <b>Sensors</b>                       | Paper out, cover open, cutter jam, paper jam and black mark detection (optional)                                                                                                                                              |
| <b>Accessories</b>                   | Data cable, power adaptor, power cord, paper roller, CD manual, Paper separator (optional)                                                                                                                                    |
| <b>OS supported</b>                  | Compatible with iOS/Android/Windows/Linux                                                                                                                                                                                     |
| <b>Safety standards</b>              | CE, FCC, RoHS, etc.                                                                                                                                                                                                           |
| <b>Printing method</b>               | Direct thermal line                                                                                                                                                                                                           |
| <b>Resolution</b>                    | 203 DPI                                                                                                                                                                                                                       |
| <b>Printing speed</b>                | 200mm/s (URL)<br>240mm/s (URL+BT/URL+WIFI)<br>300mm/s (URL+BT/URL+WIFI)                                                                                                                                                       |
| <b>Print width</b>                   | 72mm                                                                                                                                                                                                                          |
| <b>Graphics printing</b>             | Supports bitmap download and print (each bitmap size Max 20K)                                                                                                                                                                 |
| <b>Printing Command</b>              | Compatible with ESC/POS                                                                                                                                                                                                       |
| <b>Barcode</b>                       | 1D barcode:<br>UPC-A/UPC-E/JAN13/EAN13/JAN8/EAN8/CODE39/ITF/<br>CODABAR/CODE93/CODE128<br>2D barcode:QR CODE/Single USB or QR solution no QR code function                                                                    |
| <b>Character size</b>                | ANK character, Font:<br>A: 12*14dots, 1.5(W)*3.0(H)mm<br>FontB: 9*11dots, 1.1(W)*2.1(H)mm<br>Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm                                                                               |
| <b>Japanese/Korea</b>                | Optional                                                                                                                                                                                                                      |
| <b>User-defined language</b>         | PC437/Katakana/PC850/PC860/PC863/PC865/West/Europe/Greek/Hebrew/Ext1/Europe/Iran/WPC1252/PC866/PC852/PC858/Iran/Latvian/Latvian/Cyrillic/PT1511251/WPC1257/Vietnam/PC864/PC1001/Latvian/PC1001/PT1511251/WPC1257/Vietnam/Thai |
| <b>Media</b>                         |                                                                                                                                                                                                                               |
| <b>Paper type</b>                    | Thermal roll paper                                                                                                                                                                                                            |
| <b>Paper width</b>                   | 48mm/52mm/54mm/64mm/68mm/76mm/80mm (optional)                                                                                                                                                                                 |
| <b>Paper thickness</b>               | 0.06-0.08mm                                                                                                                                                                                                                   |
| <b>Paper roll diameter</b>           | 80mm Max                                                                                                                                                                                                                      |
| <b>Paper separator</b>               | support                                                                                                                                                                                                                       |
| <b>Physicall</b>                     |                                                                                                                                                                                                                               |
| <b>Dimension</b>                     | 180*142*116mm                                                                                                                                                                                                                 |
| <b>Weight</b>                        | 1.65kg                                                                                                                                                                                                                        |
| <b>Package box</b>                   | 128*123*518mm                                                                                                                                                                                                                 |
| <b>8 in carton</b>                   | 475*445*358mm/15.65kg                                                                                                                                                                                                         |
| <b>Working temperature, humidity</b> | 0 to 45 degrees centigrade, 10%~80% No condensation                                                                                                                                                                           |
| <b>Storage temperature, humidity</b> | -20 to 60 degrees centigrade, 10%~90% No condensation                                                                                                                                                                         |