

Desktop windows pos terminal all in one pc

(POS-B11.6)

Features:

pos terminal,windows pos terminal,pos terminal pc, all in one pc

Intel Celeron Processor J1900 Quad core 2.0GHz High Configuration CPU for Windows system

2.0GHz A83T ARM 8-Core Cortex-A7 Processor for Android system

2GB RAM+8GB ROM standard (Android)

2GB RAM+32GB SSD standard (Windows)

11.6 inch Multi-point capacitive touch screen

Embedded 58mm or 80mm thermal printer(Optional)

Embedded MSR RFID reader(Optional)

Stylish display panel

Applications:

Catering: hotel, restaurant, fast-food restaurant, coffee shop, bakery and cake shop

Retailer: Business Street, boutique, department store, cosmetics shop and high-class barbershop

Recreation: sauna, spa, night club, theme park, casino and point of sales for lottery ticket

Commercial: information management terminals for parking lot, inn, aviation, subway, station and wharf

Picture show:



Parameter:

Model	POS-B11.6/POS-B11.6-A
Main Board①	Intel Celeron Processor J1900 Quad core 2.0GHz (Windows)
Main Board②	2.0GHz A83T ARM 8-Core Cortex-A7 Processor (Android)
OS①	Windows7(Beta)
OS②	Android 5.1
Memory①	2GB RAM 32GB SSD (Windows)
Memory②	2GB RAM 8GB ROM (Android)
Touch Screen	Multi-point capacitive touch
Screen Size	Main screen12 inch,Vice screen 12 inch
Color	Black or White
Printer	58mm big gear thermal printer or 80mm thermal printer with Auto cutter(Optional)
I/O port①J1900	USB*4
	RJ45*1
	RJ11*1(optional)
	VGA*1
	HDMI*1(for vice screen)
	DB9 RS232 port *1,(can add 2 ports for optional)
I/O port(②A83T)	RJ11*1 (Opional)
	TF slot *1
	RJ45*1
	HDMI*1(for vice screen)
	USB*2 (can add 4 ports for optional)
	DB9 RS232 port*1
	Audio*1
	USB OTG port*1
Operating temperature	0°C to 40°C
Other Function (Android)	Bluetooth, WIFI
Optional items(Windows)	LCD VFD display,RFID,MSR camera,3G, DB25 parallel port, DB9 RS232 port*3 Other size Screen
Optional items(Android)	3G,4G camera, LCD VFD display,RFID,MSR,Other size Screen
Storage temperature	-20°Cto 60°C

Packing dimension	46*43*51cm
Power adapter	110-240V/50-60HZ AC power Input, 12/24V output depending on the printer



