

Double Line VFD POS Customer Display (Model: VFD220A)

Features:

High brightness vacuum fluorescent display for excellent visibility;

Adequately sized characters for easy viewing (9.0mm x 5.25mm);

40 characters in 20 columns by 2 lines format;

Supports a wide variety of languages with code pages;

RS232 interface or USB interface for data communication;

Power can be sourced from USB port (DC5V), no need external adapter;

Easy installation and programming;

Power on time: 30000 hours;

Command set: ESC/POS and CD5220;

Case color: black/white.

Specifications:

| Communication | |
|----------------------|--|
| Interface: | Serial port (RS-232, powered by USB), USB(Virtual COM) |
| Baud rate: | 9600bps |
| Brightness: | 700cd |
| Data bit: | 8bit |
| Stop bit: | 1bit |
| Handshake signal: | No |
| Display: | VFD Bright blue-green fluorescent display |
| Display characters: | 2 line x 20 characters / line, 40 characters, 5 x 7 Dots |
| Character size: | high 9.03mm x wide 5.25mm |
| MTBF: | 30,000 hours |
| Dimensions | |
| Panel dimensions: | 82(H) x 208(W)x30(D) mm |
| Support dimensions: | Long support: 410mm Short support: 170mm Base dimensions: 220(L) x107(w) x25(H) mm |

| | |
|---|---|
| Pitching move angle: | 45°, Can provide comfortable, and adjust the visual Angle |
| Weight: | 0.9Kg (gross) |
| Environment | |
| Operating Temp: | -20~70 A18 |
| Storage Temp; | -40~80 A19 |
| Operating Humidity: | 10~85% |
| Storage Humidity: | 10~90% |
| Command Set | |
| Adopting international standard general command ESC/POS, Its can used in DOS or Windows System Environment, Don't need any driver, Only according to the format serial order set to send data can show content. | |
| With the function of opening the cash drawer All direction adjustable. | |













Relevant documents:

[Driver](#)