58mm Thermal Printer With Built-in Power Supply

(OCPP-58X)



Product Introduction:

OCPP-58X is a well-designed economic printer for common thermal bill printing, It is adopt built-in power supply,not only can save space,but also easy for users to configure and use the printers.It's a very good choice for economical printing.

Product Features

Simple and fashion, With solid material, exquisite workmanship.

Easy paper install structure, simple and convenient to operate

Built-in power supply design, to save space and more convenient to configure;

Support multi language print, suitable for users all over the world;

Support download and print LOGO&graphics;

Application Area

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Parameters

Items		Parameters
	Printing Method	Thermal Line
	Printing Width	48MM
	Resolution	384dots/Line[]8dots/mm[]203dpi[]
Print parameters	Printing Speed	90mm/Second
	Interface Type	USB Parallel
	Line Spacing	3.75 mm[Can adjust line spacing by command[
	Line No.	Font A:32 character /Line Font B:42 character/Line Simple,traditional Chinese-16 lines
	Character	Standard GB2312 simplified Chinese Fonts
	Character Size	ANKcharacter[Font A[]1.5×3.0mm[]12×24dots[] Font B[]1.1×2.1mm[]9×17dots[] Simplified/Traditional Chinese[]3.0×3.0mm(24×24 dots[]
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/ EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151, 1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/(PC1001)/ (PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Туре	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed Method	Easy feed(Clamshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input ☐AC 100V-240V,50-60Hz Output ☐DC 12V/2.6A
	Casher Drawer output	DC 12V/1A
Buffer	Input Buffer	32 KB
	NV Flash	64 KB







OCPP-58X







Power plug for option:



Application Area:

Application scenario











