

Factory USB 80mm pos thermal receipt printer with auto cutter

(Model: OCPP-88A)

Features:

1. Unique appearance with reliable mold;
2. High-speed printing at speeds up to 300 mm / sec;
3. Optional automatic cutter;
4. Line and options Cordless Telecommunications
5. Provide a variety of interfaces: USB
6. audible alarm application support is available for the kitchen;
7. Support various types of one-dimensional and two-dimensional bar code printing;
8. Supports a variety of international languages;
9. SDK for Android provides;
10. Reliable print head life and one hundred kilometers;
11. Compatible EP SON ESC / POS command.

Parameters:

| | |
|----------------------|--|
| Printing Methods | Thermal line printing |
| Printed characters | 576dots / line (default), 512dots / line; Characters: Simplified Chinese point of 24x24, 18030 font support, support for Taiwan and Hong Kong, traditional (complex Font), ANK character; |
| Font | A: 12 * 24dots, 1.5 (W) * 3.0 (H) mm; B: 9 * 17dots, 1.1 (width) * 2.1 (H) mm Simplified / Traditional: 24 * 24dots, 3.0 (W) * 3.0 (H) mm |
| Barcode types | JUPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODABAR / ITF / CODE39 / CODE93 / CODE128, QR code |
| Print speed | 250 mm / sec as a single interface, to 300mm / sec Dual interface and triple interface |
| Interface | USB, USB + serial, USB + LAN, USB + Serial + LAN, Wireless + USB, Bluetooth + USB + LAN |
| Print command | Compatible with EPSON ESC / POS command |
| Driver | In Win9X / Window XP / Win VISTA / WIN2000 / Win2003's / Win / Win 7 8 / win8.1 / Linux is, and ESPON, SDK provides compatibility with Android. |
| Print width | 79.5 ± 0.5 mm (printing width 72) |
| Paper diameter | 83 mm |
| Paper Thickness | 0.06-0.08mm |
| Knife | Automatic cutter (optional) |
| Print Reliability | One hundred kilometers |
| Power | DC24V / 2.5A |
| Temperature | 0-45 degrees Celsius |
| In contrast humidity | 10-80% |
| Dimensions | 190 * 145 * 145 (MM) |
| Weight | 1.60 kg |

| Ordering Information | P / N | Description |
|----------------------|---------------|---|
| | OCPP-88A-U | USB ports support automatic cutter |
| | OCPP-88A-UR | USB + serial ports, supporting automatic cutter |
| | OCPP-88A-UL | USB + LAN ports support auto-cutter |
| | OCPP-88A-URL | USB + serial + LAN ports with automatic cutter |
| | OCPP-88A-W | Wireless + USB port, automatic cutter |
| | OCPP-88A-BUL | Bluetooth + USB + LAN, support automatic cutter |
| | OCPP-88A-U0 | USB port, no automatic cutter |
| | OCPP-88A-UR0 | USB + serial, no automatic cutter |
| | OCPP-88A-UL0 | USB + LAN port, no automatic cutter |
| | OCPP-88A-URL0 | USB + serial + Lan port, without automatic cutter |
| | OCPP-88A-W0 | Wireless + USB port, no automatic cutter |
| | OCPP-88A-BUL0 | Bluetooth + USB + LAN, no automatic cutter |



Relevant documents:

[*Specification](#)

[*Procedures Manual](#)

[*Instructions](#)

[*Driver WinXP Win2000 WinVista Win8-32bit of](#)

[*Driver Win8-64bit](#)

[*Linux Driver](#)

[*Printer parameter setting tool](#)

[*USB Printdemo\(Application software demo\)](#)

[*SDK For Android](#)

[*CD Files](#)