

# Fiscal supermarket a cash register machine electronic cheap desk cash register for restaurant

(M/N:POS-1520)

OCOM 1520 wide-screen POS terminal has auminium alloy base,It has intel Celeron and intel core I serie CPU for option,it is easy to acccees IO port for external devices such as thermal printer,label printer,mobile USB disk .This model is very convenient for maintenance by removing the back cover.

## Features:

15.6-inch BOE brand new LCD screen;

Multi-point projected capacitive touch panel;

Borderless screen, the front protects against direct water splashes;

Thick and stable aluminium base;

Cable management make cashier desk more tidy;

Customer display, secondary screen and MSR installation position is reserved for option.

## Specification

|                    |  |
|--------------------|--|
| Model              | POS-1520   |
| Name               | 15.6 inch Windows touch screen pos terminal  |
| Housing            | ABS plastic machine body with aluminium alloy base   |
| Color              | whole black color machine body   |
| <b>Display</b>     |  |
| Main screen        | 15.6 inch touch screen monitor   |
| Resoluiton         | 1366*768   |
| Brightness         | 250cd/m <sup>2</sup>   |
| View angle         | Horizon: 150; Vertical :140  |
| Touch screen       | Multi-point projected G+G capacitive touch   |
| Sub-display        | 13.3 inch display, W or W/o touch function, resolution 1366*768                              |
| Customer display   | 2*20 VFD or 2*20 LCD mounted to back cover for option  |
| <b>Performance</b> |  |
| Motherboard        | Intel Celeron Bay Trail J1900 2.0GHz,or,intel core I3 / I5 CPU for option                    |
| System Memory      | 1*SO-DIMM DDR3 slot, 4GB DDR3L /1333MHZ,8GB for option                                       |
| Storage device     | Msata SSD 64GB or higer, up to 256GB   |
| Audio              | On board Real Tek ALC662   |
| LAN                | 10/100Mbs,Realtek RTL8111F Lan chip<br>built in Mini PCI-E slot,support embedded WIFI module |

|                          |  |
|--------------------------|--|
| Operating System         | Windows7/8/10, Embedded,WEPOS,Linux                        |
| <b>Connectivity</b>      |  |
| External I/O port(J1900) | Power switch*1,12V DC in Jack*1                            |
|                          | LAN:RJ-45*1  |
|                          | USB *6   |
|                          | COM(RS232) * 1,Can be expanded more RS232 ports for option |
|                          | VGA(15Pin D-sub)*1   |
|                          | Audio out*1,MIC in*1                                       |
| <b>Options</b>           |  |
| MSR                      | optional side MSR  |
| <b>Package</b>           |  |
| Weight                   | Net 4.0Kg, Gross 6.0Kg                                     |
| Package with foam inside | 460*295*415mm  |
| <b>Environment</b>       |  |
| Operating temperature    | 0 to 40 degrees centigrade                                 |
| Storage temperature      | -10 to 60 degrees centigrade                               |
| Working humidity         | 10%~80% No condensation                                    |
| Storage humidity         | 10%~90% No condensation                                    |
| <b>Accessories</b>       |  |
| Power adapter            | 110-240V/50-60HZ AC power input ,DC12V/5A output adaptor   |
| Power cable              | Power cable plug compatible with USA /EU / UK etc          |



































