

Flatbed laser 32 bit omnidirectional barcode scanner rs232 USB

□OCBS-T009□

Specification

| PERFORMANCE PARAMETERS | |
|----------------------------|---|
| Light Source | Visible Laser Diode 650nm |
| Line | 20 lines |
| Scan Rate | 1800 scans per second (Omni-directional) |
| Scan Pattern | Omni-directional: 5 fields of 4 parallel lines |
| Print Contrast | 32% minimum reflectance difference |
| Decode Capability | EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN 128, ISBN,ISSN, Codabar, Code 25 non-interleaved, Code 25 interleaved , Matrix 2 of 5, MSI, PostBarcode, etc |
| ELECTRICAL PARAMETERS | |
| Support Interface | PS/2, USB 2.0, RS232 |
| Voltage Power | 5VCD±12% 1.6W |
| Laser-level | Class2 |
| Certificate | FCC, CE |
| LED Indicator | Red and Blue |
| PHYSICAL PARAMETERS | |
| Weight (pc) | N.W: 474g/pc G.W: 819g/pc |
| Size (pc) | Host: 115mm*110mm*152mm Package: 245mm x165mmx132mm |
| Weight (Carton) Package | 9.6 kg/10pcs |
| Size (Carton) | 680mm*350mm*280mm |
| ENVIRONMENTAL PATAMETER | |
| Crash resistant | Can withstand 1.5M free fall |
| Operating Temperature | 0 to 40 Degrees (32 Fahrenheit to 104 Fahrenheit) |
| Storage Temperature | -40 to 60 Degrees (-40 Fahrenheit to 140 Fahrenheit) |
| Humidity | 5% to 95% Relative humidity, Non-condensing |
| Sealed Environment | IP54 (Sealed to resist airborne particulate contaminants) |

