

Free driver cheap price pos 80mm thermal printer  
(OCP-80G)

**Features:**

- 1.Desktop or wall-mounted type for option.
- 2.Supports multi 1D barcodes and QR codes printing.
- 3.100M Ethernet port, ultra high speed data transmission.
- 4.Supports 256KB NV Logo storage and 2M big buffer memory.
- 5.Supports black mark detection and order reminding function, compatible with OPOS driver.
- 6.Supports printing status monitor and anti-losing order function.
- 7.3 interface 260mm/s printing Speed

**Parameters:**

thermal printer,printer thermal 80mm,pos 80 printer thermal driver

|                      |                                                                                                                                                                                                                                        |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Printing method:     | Direct thermal                                                                                                                                                                                                                         |
| Printing speed:      | 230mm/s □260mm/s                                                                                                                                                                                                                       |
| Roll width:          | 79.5±0.5mm                                                                                                                                                                                                                             |
| Print diameter:      | Φ80mm                                                                                                                                                                                                                                  |
| Paper thickness:     | 0.06-0.08mm                                                                                                                                                                                                                            |
| Column capacity:     | 576dots/line512 Dots/line                                                                                                                                                                                                              |
| Line's pacing :      | 3.75mm□Adjustable by commands□                                                                                                                                                                                                         |
| Print command:       | Compatible with the ESC/POS command                                                                                                                                                                                                    |
| Interface type:      | Serial+USB+Lan/36P parallel port/25P serial +USB/LAN                                                                                                                                                                                   |
| Cutters life:        | 1million cuts                                                                                                                                                                                                                          |
| Print head life:     | 100 km                                                                                                                                                                                                                                 |
| Input buffer :       | 2048Kbytes                                                                                                                                                                                                                             |
| NV Flash:            | 256Kbytes                                                                                                                                                                                                                              |
| Power adaptor:       | AC110V/240V□50~60Hz                                                                                                                                                                                                                    |
| Power supply:        | DC 24V/2.5A                                                                                                                                                                                                                            |
| Cash drawer supply:  | DC 24V/1A                                                                                                                                                                                                                              |
| Work environment:    | Temperature(0□45) humidity(10□80%)□Non- condense□                                                                                                                                                                                      |
| Work environment:    | Temperature(0-45) degree centigrade, humidity(10-80%) Non- condense                                                                                                                                                                    |
| Storage environment: | Temperature(-10□60℃); Humidity(10□90%)                                                                                                                                                                                                 |
| Character size:      | ANK□FontA:1.5*3.0mm/ FontB□1.1*2.1mm                                                                                                                                                                                                   |
| Barcode:             | UPC-A/UPC-E/JA□EAN13□/JAN8□EAN8/CODE39/ITF /CODE93/CODE128/QRCode/PDF417 (options)                                                                                                                                                     |
| Characters:          | PC347□Standard Europe□□Katakana□PC850□Multilingual□□PC860□Portuguese□□PC863 □Canadian-French□□PC865□Nordic□□West Europe□Greek□Hebrew□East Europe□Iran□WPC1252□PC866□Cyrillic#2□□PC852□Latin2□□ PC858□IranII□Latvian□Arabic□PT151□1251□ |

Physical characteristics Weight: 1.25Kg; Appearance size: 190×145×143mm (length \* width \* height)

**Product Show:**

thermal printer,printer thermal 80mm,pos 80 printer thermal driver







[www.ocominc.com](http://www.ocominc.com)

CE FCC





**Relevant documents:**

[\\*Specification](#)

[\\*IP Address Configure Manual](#)

[\\*Instruction Manual](#)

[\\*Driver for all windows system](#)

[\\*Driver for Linux](#)

[\\*Printer Parameters Setting Tools](#)

\*CD Files