

|                               |  |
|-------------------------------|--|
| Model                         | POS-T2Pro  |
| Name                          | 5.5 inch capacitive touch screen, support the electronic signature |
| Battery                       | 3.8 V /6400mAh   |
| Power Adapter                 | Input□100-240V, 50/60Hz,1.5A,Output□5V DC /2A                      |
| Charger interface             | USB type C   |
|                               |  |
| Main screen                   | 5.5 inch HD touch screen dispaly                                   |
| Resolution                    | 720*1280 IPS   |
| <b>Performance</b>            |  |
| CPU                           | octa-core,SC9863, Cortex-A55 ,1.6GHz processor                     |
| RAM                           | 3GB  |
| Flash                         | 16GB Flash   |
| Communication                 | 2G/3G/4G   |
| Operating System              | Android 12   |
| Button                        | Power button, Scan Button,Volume button                            |
| Bluetooth                     | Bluetooth 4.0  |
| WIFI                          | WIFI 802.11 b.g.n.ac   |
| Printer                       | 58mm Thermal Receipt and label Printer                             |
| Paper Roll                    | Width: 58mm; Diameter: ≤40mm                                       |
| Scanner                       | 5 Mega-pixel Camera decoding, 2D Scanner (Option)                  |
| NFC                           | Support ISO/IEC 14443A&B, Mifare, felica card                      |
| SIM slot                      | Sim*2 (default) or Sim*1+Sam*1 for option                          |
| Speaker                       | Digital Audio speaker  |
| Fingerprint                   | FBI/STQC Fingerprint (Optional)                                    |
| GPS or AGPS                   | Support GPS+AGPS   |
| MDM                           | Support  |
| <b>Peripheral Accessories</b> |  |
| Accessories                   | USB Type C*1   |
|                               | Charging adapter*1   |
|                               | user manual*1  |
| <b>Environment</b>            |  |
| Operating temperature         | 0 to 40 degrees centigrade   |
| Storage temperature           | -10 to 60 degrees centigrade                                       |
| Working humidity              | 10%~80%  |
| Storage humidity              | 10%~90%  |