


High Quality 58mm Android or IOS Bluetooth Thermal Printer

(Model: OCPP-M03)

Specification:

| | |
|---------------------------|--|
| Overall Dimension (W×D×H) | 105×75×45mm |
| Weight | 134g |
| Color | Black |
| Effective print width | 48mm |
| Print method | Thermal line printing |
| Print commands | ESC/POS compatible command set |
| Print speed | Up to 90mm/sec |
| Resolution | 8 dots/mm(203dpi) |
| Print font | 12x24/ 24x24 |
| Column capacity | 32 columns/ 16columns |
| Character size | 1.5 x 3.0 mm(W x H)/ 3.0x3.0mm(WxH) |
| Paper dimensions | 58.0±0.1mm x diameter 40.0mm |
| Paper thickness | 0.06 to 0.08mm |
| Character set | Alphanumeric/ Chinese Kanji |
| Interface | USB, RS-232, Bluetooth (optional) |
| Flash | 256KB |
| Power Adapter | 9V DC/2A |
| Battery Power | 7.4V DC/ 1500mA; battery can stay by for 4-5 days, when it is full power, it can print 120-150m paper |
| Other features | Paper detection, power detection, Manual shut down |
| Working conditions | Temperature:-10degree C~50degree C, Humidity:10%~90% |
| Storage conditions | Temperature:-20degree C~70degree C, Humidity:5%~95% |
| Device name | Can be customized, letter and digital for option, at max 30 ASCII characters. |
| Password | Enter default pairing code "1234", it can be customized. At max 6 digitals. |
| Power plug dimension | 3.5*1.1mm |



Relevant documents:

Do you want to know more product information? Please Click here. 

Specification

User's Manual

[SDK](#)

Related Videos:

[Setup the battery for the 58mm blue tooth printer \(OCPP-M03\)](#)

