

30x2 Characters Double Line LCD Customer Display

(ModelNo.:OCPD-LCD230C-C1)

Features:

Supports 11 command modes included EPSON etc.

Compatible with 95 national languages;

Power supply from 5V to 24V to prevent any mindless use of improper power input;

Can show 2 lines * 30 columns or 2 lines * 15 Chinese;

OPOS/JPOS driver is standard.

Data sheet:

General	Display method	TN-LCD negative display (White on the Blue background)
	characters	30 columns*2 lines or 20 Chinese*2 lines
	brightness	1200cd/m2
	Character font	16*16 dot matrix
	Character type	95 Alphanumeric32 international characters
	Character Size	9.92[H]x4.75[W]mm Chinese: 9.92*9.5mm
	Dot size[X*Y]	0.426(H) x 0.6(V)mm
	Window size	142.7(H) x 19.82(V)mm
	PCB Size	160[L]x36.6[W]x10.1[H]mm
	Weight	Approx.65.5 grams
Commands Mode		LD220[EPSON POS D101]AEDEX[UTC/S][UTC/P] ADM788[DSP800]CD5220[EMAX]LOGIC CONTROL
Language Support		FRANCE[GERMANY[U.K.]DENMARKI[SWENEN]ITALY[SPAIN]APAN[NORWAY][DENMARKII[SLAVONIC[RUSSIA[Portuguese[Canadian French[Nordic[Turkish[Greek West European Latin.CP858[CP860[WCP1252[CP857[TURKISH[Polish[WPC1250[WPC1253[GREEK[WPC1255[Hebrew[WPC1251[CP866[CP852[CP737 [DOS greek[CP858[CP864[Arabic[Farsi[Iran[CP936-GBK, Chinese Traditional, Chinese Simplified
Interface		RS-232[serial]or USB Virtual COM
Connection	Baud	Direct connection 9600 or 19200 bps
Reliability	MTBF	30000 hours
Power	Consumption	5-24 VDC
Safety	EMC standards	FCC[CE[ROHS
	Safety standards	

