Truck Bus 3 track mini MSR card reader and TTL UART USB (Model: CR1300)

Specifications:

Dimension	90 mm (l) x 26 mm (v	90 mm (I) x 26 mm (w) x-rayed mm (h)		
Weight	85 grams (approx.)			
Power	+ 5 V Dv			
Power	40mA (max)			
Operation Trajectory	Indoor use	Indoor use		
Card Standard	lso778112	lso778112		
Orbital position	ISO 1 (IATA)	ISO 2 (ABA)	ISO 3 (MINT)	
Recording density	\$number BPI	\$number BPI	\$number BPI	
Record capacity	79 characters (7bits)	40 characters (5bits)	107 characters (5bits)	
Interface	/serial Port	/serial Port		
Card thickness	Plastics 0.76 08mm	Plastics 0.76 08mm		
Head function	Read only 1.5mm			
Operating speed	10 ~ 150 cm/sec			
The life of the head	500,000 passes (1 pass: one card)			
Error rate	Less than 0.5% (Exchange test Card)			
Temperature	Storage: 10 to + 70 o	Storage: 10 to + 70 operation: 20 to + 70		
Humidity	Storage: 0% to \$num	Storage: 0% to \$number RH operation: 20% to \$number RH		

Product Details:

x|x|x|x|x|x|x|x|x|x|x|x|Related documents:

Do you want to know more product INFInformation?Please Click here.

Specification User manual Sdk